First Copy TECHNOLOGY DEPARTMENT

### Construction MAY 1 5 193 1930 Methods



A MONTHLY REVIEW OF FIELD PRACTICE AND EQUIPMENT

General Construction Highways Buildings Engineering Industrial



Con

Bui are of a inte tion exec tive pruc pres is ir since R

than hand the and favo build time tion prud week only ditio stabi

Buil

as co

With at a l with to ma


const

foreg comm Build agree buyer been

CONSTRUCTION METHODS, May, 1930. Vol. 12, No. 5. Published monthly. McGraw-Hill Publishing Company. Inc., Tenth Avenue at Thirty-sixth Street, New York, N. Y. \$1 per year; 10 cents per copy. Entered as second-class matter, October, 1926 issue. Vol. 8, No. 19, at the Post Office at New York, N. Y., under the Act of March 5, 1879. Printed in U. S. A.

May, 1930—CONSTRUCTION METHODS

TECHNOLOGY &



#### Conditions Favorable for Residential Construction

AGGING behind other types of construction during recent months residential building now faces conditions which the National Building Survey Conference believes are favorable, from the point of view of the home-owner, for a resumption of activity in this field. Of particular interest to the contractor is the assertion that banks and loan associations, executing an about-face, are now actively seeking outlets for their funds in prudent home-building projects. The present attitude of the lending agencies is in decided contrast to their position since the slump in the stock market.

Right now, therefore, the constructor has an opportunity to sell more than his own services. There is at hand ample evidence to support him in the contention that money conditions and material prices at present are as favorable to the prospective homebuilder as they are likely to be for some time to come. If the seasonal resumption of residential building, wherever prudent, can be advanced by a few weeks it will contribute materially not only to the improvement of local conditions but also to general business stabilization.

640

#### More for the Building Dollar

Along lines similar to those in the foregoing note discussion at a recent committee meeting of the New York Building Congress brought out general agreement on the proposition that buyers of new buildings this year have been enjoying bargain days in so far as construction service is concerned. With employment in the building trades at a low ebb throughout the winter and with many contractors seeking work to maintain their organizations, owners have been able to place contracts for construction at prices substantially below normal. Another favorable factor

#### CONSTRUCTION METHODS

A monthly review of modern construction practice and equipment

ROBERT K. TOMLIN. Editor

Editorial Staff

VINCENT B. SMITH NELLE FITZGERALD J. I. BALLARD (San Francisco)

WILLARD CHEVALIER, Publishing Director

A McGraw-Hill Publication Tenth Avenue at 36th Street, New York

this year has been an increased output per worker; when men on the job realize that others are lined up waiting to take their places the minute a vacancy occurs there is little tendency

A third factor relates to improvement in quality of work. Slackening in construction during the winter forces a certain number of skilled men-foremen, mechanics and others -into the ranks of common labor. From men of this sort, normally employed in a supervisory capacity, it is natural to expect a higher grade of work than from ordinary labor. All of these conditions have combined, therefore, to give the owner more for his building dollar than he usually receives.

#### Announcing a Series on Railroad Construction

This month's issue contains the first of a series of articles on "Railroad Construction in Mountain Country," by Vincent B. Smith, assistant editor of Construction Methods. The series will illustrate and describe in detail the methods employed today by a number of contractors in tunnel driving and grading for several important number of contractors in tunnel driv-ing and grading for several important branch lines penetrating the central portion of the Appalachian Range. Photographs and data will be pub-lished in sufficient amount to afford a ready comprehension of the adapt-ability and advantages of the various practices in blasting, everagating haulability and advantages of the various practices in blasting, excavating, hauling, and tunnel construction. The articles, furthermore, will give an insight into the organizing and equipping of jobs for large- and small-scale grading and tunneling operations.

#### Increased Federal Aid

DDITIONAL stability and continuity have been built into the nation's road program by the \$50,000,000 annual increase (for three years) in federal-aid highway funds, provided for in the measure passed by Congress and approved by the President April 4. Specifically, the new act authorizes federal aid to the extent of \$125,000,000, instead of the former \$75,000,000, for each of the fiscal years 1931-33, inclusive. As in the past, the federal funds, matched by equal amounts from the states, must be spent upon a designated system of primary routes constituting 7 per cent of the total highway mileage. In those states that have completed the surfacing of their 7-per cent systems, six in all, the allowable amount of federal aid that may be expended per mile of road is increased to \$25,000, as compared with \$15,000 under former regulations.

Coming at a time when the nation is looking to the construction industry to help relieve present conditions of unemployment the increased participation of the federal government in the cost of trunk line routes will have a generally stimulating effect. While the larger federal allotment is a comparatively small percentage of the total annual expenditures for highway improvement the new act has other influences of far-reaching importance. Primarily it gives continued assurance of proper selection and coordination of routes, sound design and construction and adequate engineering supervision in all states availing themselves of federal aid.

#### Higher Steel Stresses

New York City's revised building code, effective March 25, permits an 18,000-lb. unit working stress for steel frame structures instead of the former 16,000-lb. unit stress. The amended code also sanctions the use of alloy steels.

#### To Save Real Money

TODAY we hear much about the need for intelligent selling. Seldom, however, do we hear very much about intelligent buying. Yet from the nature of things, sound selling and sound buying must move hand in hand if progress is to be made.

Mr. E. F. Watkins is the purchasing agent for the Southern California Edison Company. Speaking before the Purchasing Agents Association of Los Angeles, he offered the following comment on this subject:

"The practice of price jobbing, playing one bidder against another, and all the attendant evils of special, illegitimate discounts, rebates, rejected merchandise, damage claims, and so forth, is widespread and will be difficult to eradicate, especially in the smaller organizations, because of the calibre of the men involved who look upon any saving made in this way as a direct contribution to their own profit.

"The straight-thinking buyer can effect great savings through knowing what to buy and when to buy, by simplifying and standardizing his purchases, and thus be a material aid to his entire organization. But one of these 'smart boys' who is misled into spending all his thought and energy in scheming to beat down legitimate prices to a basis where the seller is deprived of all profit is fooling himself and his company as to the savings he effects, and frequently gets everybody into trouble. The worst feature of this, from an economic standpoint, is that he is neglecting the opportunity which nearly always exists to a greater or lesser degree to save real money along constructive lines."

Construction Methods tries through its editorial and advertising pages to keep the "straight-thinking buyer" posted on what is available to do his job most efficiently. And in doing this consistently we hope to increase the opportunities "to save real money along constructive lines."



#### McGRAW-HILL PUBLISHING COMPANY, INC., TENTH AVENUE AT 36TH STREET, NEW YORK, N. Y. CABLE ADDRESS: "MACHINIST, N. Y."

James H. McGraw, Chairman of the Board
Malcolm Muir, President
James H. McGraw, Jr., Vice-Pres. and Treas.
Edward J. Mehren, Vice-President
Mason Britton, Vice-President
Edgar Kobak, Vice-President
Harold W. McGraw, Vice-President
H. C. Parmeler, Editorial Director
C. H. Thompson, Secretary

Member A.B.C. Member A.B.P. New York District Office, 285 Madison Avenue
Boston, 1427 Statler Building
Washington, National Press Building
Chicago, 520 North Michigan Avenue
Philadelphia, 1600 Arch Street
Detroit, 2-257 General Motors Building
Dallas, 303 Thomas Building
Cleveland, Guardian Building
Greenville, S. C., 1303 Woodside Building
St. Louis, Bell Telephone Building
San Francisco, 883 Mission Street
Los Angeles, 632 Chamber of Commerce Bldg.
London, 6 Bouverie Street, London, E. C. 4

Copyright, 1930, by McGraw-Hill Publishing Company, Inc.

### When y

#### you plan for Airport Grading-

Do as they did at the Curtiss Airport at Glenview, Ill., and skimming cuts and shallow excavation will cost you less. There the contractor used a Haiss Excavator for all the heavy grading, digging runways, hangar foundations, etc. They were even able to dig right through the burned debris and old foundations of a couple of farmhouses. In clay, sometimes hard and dry but often waterlogged, the machine averaged 500 yards per 9 hour day, loading dump wagons. If you use trucks you'll work the machine faster—see Bulletin 629.

GEORGE HAISS MANUFACTURING CO., INC.
139th St. & Canal Place, New York
Representatives in Principal Cities



Opening the Indian trail for the pleasure car is play for these 6-cylinder, 5-ton, 114-inch wheelbase Autocar Trail Blazers (Model SHS) of the Stamford Road Construction Company, Stamford, Conn.

### WHERE THE GOING IS ROUGH



Where the going is rough use Trail Blazers. You can't beat them for performance in close quarters. Transforming cowpaths, Indian trails and narrow country roads into wide modern concrete highways is "duck soup" for the Trail Blazer group of the precision-built Autocar trucks.

Changing country roads along beautiful Lake Ticonderoga into modern highways is exactly what the Stamford Road Construction Company of Stamford, Conn., has been doing with its Autocar Trail Blazer fleet. Turning on the brim of a hat, they have proved so well adapted for their work that they have won a strong preference with this user.

Autocars are made in conventional as well as engineunder-the-seat models. You may choose from 49 chassis designs according to the nature of the job you have to do.

Write for the Autocar Construction Booklet



AUTOCAR TRUCKS
The AUTOCAR Company, Ardmore, Pa., Established 1897

# Any operator can understand the NORTHWEST OIL ENGINE DEST

No intricate or delicately adjusted metering devices!

No high pressures or high pressure pumps to cause trouble!

No injectors to clog with the resulting loss of power!

No difficulties because of crankcase dilution!

No difficulties in securing clean fuel!—and gasoline engine dependability at all times!

#### NORTHWEST ENGINEERING CO.

The world's largest exclusive builders of gasoline, oil burning and electric powered shovels, cranes and draglines 1728 Steger Building 28 East Jackson Boulevard Chicago, Illinois, U. S. A.



NORTHWEST

### ROP Blue Center Steel Wire Rope

HEN maintenance cost is lowered and capacity is increased at the same time, every executive and operating engineer is interested in the product which produces these results.

Replacements are annoying and expensive, the long life of "Blue Center" Steel Wire Rope reduces the number of replacements and thus lowers the operating cost. It is particularly adapted to heavy-duty construction work where the ropes are subjected to severe strains; sudden jerks; and excessive loads.

Our Engineering Department will be glad to give special consideration to your wire rope problems.




#### UNIVERSAL TRUCK CRANE


How Can You Get Along Without This Versatile Machine?

A 1/2 yard digging and material handling unit. Travels at motor truck speed on the highway. Eight fully rubber-tired wheels reduce wheel loads—strictly in keeping with modern lowered wheel load requirements.

Off the highway it travels on its own steel pavement. The Motor Truck (Christie) Crawler is put on or off as easily as a set of tire chains. And it takes the machine through mud, over uneven ground—anywhere there's a crane job to be done. (Exclusively applied to Universal Truck Cranes)

THE UNIVERSAL CRANE COMPANY LORAIN, OHIO






UNIVERSAL

Doing a double job.

20 miles



The pipe used was 48 inch heavy, cast ironprobably the world's longest pipe job using this heavy type of cast pipe.

Section by section the Link-Belt Trench Hoes dug the trench then swung the 7-ton pipe into place. Twenty-seven sections per day of trench (7 feet wide at bottom), and pipe laid, was not unusual, in spite of 15 to 20% grades and often wet digging.

This was another job handled by Pepper Bros., the popular contractors of Syracuse and Albany, New York, now using five Link-Belts. Out of

long experience, Mr. Vic Pepper wrote: "Link-Belts may be more expensive than some of the others, but by far they are the cheapest to operate."

The Link-Belt through-and-through quality in Shovel-Crane-Dragline units will lower your yardage and handling costs. Gasoline, Diesel, or electric power.

Shovels—Cranes—Draglines of 3/4 to 2 yd. capacity, heavy duty units

LINK-BELT COMPANY

Builders of Locomotive Cranes for 30 years. Portable Loaders—Crawler Cranes—Shovels—Draglines

Offices in Principal Cities CHICAGO, 300 West Pershing Road



### ONLY ONE OPERATING CLUTCH ON THIS GAS SHOVEL

Five years ago Bucyrus-Erie announced the world's first Gas+Air shovel—widely acclaimed because it combined the convenience of gasoline power with the flexibility, ease of control, simplicity, and speed of the modern steam shovel.

Gas+Airs have proved their dependability beyond a doubt—proved that no other gasoline machine can equal their output... Three separate engines—a gas engine for the hoist, and two air-engines, one for the crowd and one for the swing, give this gasoline machine the flexibility and accurate control of a steam machine.

Full 100% power of the gas engine is available when needed for hoisting through hard materials. The direct-connected crowd and swing air-engines give speed and smoothness unheard of with clutch-type machines.

And now an equally successful development — Diesel +Airs. These two amazing machines are revolutionizing excavating costs. Only Bucyrus-Erie builds Gas+Airs and Diesel +Airs. Write for bulletin.

Representatives throughout the U. S. A. Offices or distributors in all principal countries. Branch Offices: Boston, New York, Philadelphia, Atlanta, Birmingham, Pittsburgh, Buffalo, Detroit, Chicago, St. Louis, Dallas, San Francisco.

BUCYRUS-ERIE COMPANY, manufacturers of the only complete line—all sizes, types and powers. Plants: South Milwaukee, Wis.,

South Milwaukee, Wia., Eric, Pa., Evansville, Ind. General Offices: South Milwaukee, Wisconsin. BUCYRUS

A-80-5-30-CM

### Punching piling down—and pulling them with a real extractor

Years of experience in pile hammer designing and building are back of Warrington-Vulcan Pile Hammers, and their superior service to the contractor has made them a standard of the industry.

Warrington-Vulcan Pile Hammers are "the hammers with the true punching action." Incorporating the exactly correct driving principles, they sink piling faster, without damage to pile heads. Upkeep of the hammer is also lower.

Freedom from operating troubles; low operating

cost; an exceedingly simple and positively actuated valve gear; short steam passage to save steam—these are other hall-marks of Warrington-Vulcan Pile Hammer efficiency.

The Vulcan Pile Extractor is America's only exclusive Extractor. It is always ready for immediate service. Requires no "harness" nor laborious adjustments. Low in first cost and upkeep. Made in three sizes for pulling the heaviest and most difficult wood and steel piling.

#### VULCAN IRON WORKS

327 N. Irving Avenue, CHICAGO



#### WHY AN OWEN LASTS

LONGER . . THE OWEN method of keeping the grease in and the grit out of the center shaft bearings means steady, economical operation, longer life for the bucket and low upkeep costs.


The Owen main shaft construction eliminates all wear from castings and provides gritproof lubricated bearings. The outside pair of hinges are pinned to the shaft; the inside pair are bushed. The faces of the hinges are protected by heavy renewable washers fitted between the counterbored faces of the castings. These washers seal the bearings from grit and are completely lubricated by Alemite, which forces grease out from the center of the bearings.

There are 16 more good reasons why Owen Buckets do a better and bigger job in less time and have greater durability. Send for an Owen folder giving details.

#### THE OWEN BUCKET COMPANY

6023 Breakwater Avenue


Cleveland, Ohio



#### 17 POINTS OF LEADERSHIP

- 1. One-piece steel cross-head.
- 2. No wear in upper or lower arm ends.
- 3. Heavy high carbon steel arms.
- 4. Adjustable undiminished closing power.
- 5. Long life to sheaves and cable.
- 6. Long arm bolt bearings sealed from grit.
- 7. Lever type steel arm brackets.
- 8. Closing cable is protected against exces-
- 9. Heavy shock-resisting renewable lips.
- 10. Cable clips eliminated.
- 11. Sealed center shaft bearings.
- 12. Greater digging power with no dead
- 13. Penetration and clean dumping.
- Dropping shocks absorbed, eliminating breakage.
- 15. Rigid shell construction.
- 16. Heavy duty high carbon drop-forged steel
- 17. Lips or teeth points hit first.





#### CARNEGIE Steel Sheet Piling

9

WITH the recent introduction of several new sections, Carnegie Steel Company is now prepared to supply steel sheet piling eminently suitable for any driving condition. All sections are characterized by short stiff interlocks to give strength against pulling apart, yet providing sufficient clearance for ease of driving and flexibility of joints. The circuitous route which water must travel through the interlock affords opportunity for lodgment of solid materials in the interlock, insuring practical watertightness.

Our engineers are at your service and will gladly consult with you on problems involving your steel requirements.

Section	Driving Width	Web Thickness	Weight per Foot	Weight per Square Foot of Wall	Section Modulus per Single Piece	Section Modulus per Foot of Wall
M 106	14 in.	3% in.	36.9 lb.	31.6 lb.	10.34 in.8	8.86 in.
M 107	15 in.	3/8 in.	38.4 lb.	30.7 lb.	4.10 in.8	3.28 in.
M 108	15 in.	1/2 in.	42.8 lb.	34.2 lb.	4.10 in.8	3.28 in.8
M 110	16 in.	31/64 in.	42.6 lb.	32.0 lb.	20.34 in.8	15.26 in.8
M 111	16 in.	3% in.	29.3 lb.	22.0 lb.	7.74 in.8	5.80 in.8
M 112	16 in.	3/8 in.	30.6 lb.	23.0 lb.	2.50 in.8	1.88 in.8
M 113	16 in.	1/2 in.	36.2 lb.	27.2 lb.	3.28 in.3	2.46 in. <sup>3</sup>

#### CARNEGIE STEEL COMPANY

Subsidiary of United States Steel Corporation


PITTSBURGH , PA.

56

#### CARNEGIE STEEL SHEET PILING



## New in Periormance New in Performance



Novo Roller Ring Pump mounted on special rubber tired trailer with combination tongue and prop

ROLLER RING

### No Diaphragm No Packing No Oil Seal

There is no other pump anywhere like this new Novo Roller Ring Pump.

It has no packing—no glands—no oil seal—no diaphragm to require attention.

Yet the single, vertical pump has a capacity of 3500 to 5000 gallons per hour—develops a 75' head. Other sizes, available later, will have even greater capacities.

#### **Entirely New**

The principle of this Novo is entirely new. Two rubber rings on the plunger roll with the action of the piston. They do not slide.

These rolling rubber rings, pressed against the cylinder wall and piston, make an absolutely liquid-tight seal.

As the Roller Rings roll, they are subjected to no sliding friction. Wear is minimized to a point where it need not be considered.

The Roller Rings are guaranteed for a season's work without replacement.

Straight Line Flow—High Velocity
Due to the short rank strokes of the
plunger—and the straight line flow from

suction to discharge—the water is forced through the pump at a higher and more uniform velocity than in the ordinary diaphragm or plunger diaphragm. This permits the handling of more foreign matter in suspension without damaging the pump.

For the same reason, this pump more nearly approaches a perfect vacuum than other types, making it ideally suited for handling well points.

Novo Roller Ring Pumps are self-priming, compact, and light in weight. They are fitted with steel hinge valves faced with special composition rubber. Valve seats are set at an angle.

The pumps are applicable to all kinds of de-watering jobs, replacing centrifugal, diaphragm and plunger pumps. On certain jobs, the Roller Rings replace pressure pumps.


Write for the special folder and complete details on this greatest modern pump development.

#### NOVO ENGINE CO.

214 Porter St., Lansing, Michigan Clarence E. Bement, Vice-Pres. and Gen. Mgr.



Note the straight line flow from suction to discharge — and the liquid tight seal produced by the two roller rings on the plunger of the new Novo Roller Ring Pump.



Patent pending



#### LACKAWANNA STEEL SHEET PILING



### used in large cellular Cofferdam for constructing U. S. Government Lock and Dam, Hastings, Minn.



This 775- x 220-foot cofferdam, with a 300- x 200-foot wing at one end, was constructed with Lackawanna 8½-in. x ½-in. Straight-Web Piling. There were 86 circular cells, 12 ft. 4 in. dia., joined by short diaphragms of two to four sheet piles. The piling was 25 feet long on the inner side and 40 feet long on the outer side of the cells. In addition a permanent cut-off wall 4,000 feet long was driven, using 25-foot and 40-foot lengths of piling.

The piling was driven through river silt, hard clay and sand, with occasional submerged timbers. The maximum depth of water was 20 feet. Although more than 8,000 sheet piles were driven, only one interlock was pulled apart. The piling was assembled in threes at the mill. The job superintendent estimated that the cost of assembling and driving was reduced 20 per cent due to this pre-assembly.

Three 10-inch pumps were used to unwater the cofferdam. When unwatered, one pump, operating at half capacity, was ample to keep the cofferdam dry.

Contractors—
Fegles Construction Company
Minneapolis, Minn.

#### BETHLEHEM

BETHLEHEM STEEL COMPANY General Offices: Bethlehem, Pa.

District Offices: New York, Boston, Philadelphia, Baltimore, Washington, Atlanta, Pittsburgh, Buffalo, Cleveland, Cincinnati, Detreit, Chicago, St. Louis.

Pacific Coast Distributor: Pacific Coast Steel Corporation, San Francisco, Los Angeles, Seattle, Portland, Honolulu.

Export Distributor: Bethlehem Steel Export Corporation, 25 Broadway, New York City.

COL

### WHERE TRUCKS CANNOT OPERATE THE LINN MAKES MONEY

Sure-footed and with an over abundance of power, the Linn wastes no time between shovel and dump. Watch its patented flexible traction grip into the rubber-like gumbo and carry on with the certainty of a wheel truck on a good road.

See the shovel deliver tons of heavy earth or rock into its wide body, and then... watch the Linn move away without a protest, over "tough going" to its destination. In a moment it is on its return, backward if the distance is short or the space narrow. Forward or reverse, it travels with equal speed and ease of handling.

Day after day, regardless of the job's demands, weather or ground conditions, the Linn carries on where trucks could not turn a wheel... and makes money for its owner. Learn more about Linn performance and profits. Write or wire for data. AS IT LAYS ITS



#### LINN MANUFACTURING CORPORATION

Division of LAFRANCE-REPUBLIC Corporation


Manufacturers of American-LaFrance Trucks, Linn Tractors, Republic Trucks

Factories: Alma, Mich. . Morrie, New York

New York City Elmira, N. Y. Pearl River, N. Y. Watertown, N. Y. Gloversville, N. Y. Baltimore Boston Charlotte, N. C. Memphis, Tenn. Johnson City, Tenn. Philadelphia Represented in:
Pittsburgh
Louisville, Ky.
Detroit
Chicago
St. Louis
Kansas City, Mo.

Little Rock, Ark. Tulsa, Okla. Omaha, Nebr. Sioux Falls. S. D. St. Paul, Minn. Salt Lake City Denver
Jerome, Ariz.
Los Angeles
San Francisco
Portland, Ore.
Spokane





#### Wherever vhatever – men build

- when great construction must be time-scheduled, operation by operation, and actual costs must be kept within narrow estimates, the indispensable, fundamental essential is not only equipment performance, but staunch, loyal, unfailing dependability!

> Above all things N. E. C. equipment is built to be trustworthy, to stand behind its owner in doing its job, and keep doing it, without disorganizing delays and behind it is N. E. C. Service, in itself an unequalled value to the equipment

> > owner.

#### N. E. C. Lines

#### **KOEHRING**

Pavers, Mixers; Power Shovels, Pull Shovels, Cranes, Draglines; Dumptors.

#### **PARSONS**

Trench Excavators, Backfillers.

#### INSLEY

Excavators; Concrete Placing Equipment, Cars, Buckets, Derricks.

#### C. H. & E.

Portable Saw Rigs, Pumps, Hoists, Material Elevators.

#### T. L. SMITH

Tilting and Non-tilting Mixers, Pavers, Weigh-Mix.

#### KWIK-MIX

Mixers: Concrete, Plaster and Mortar.





### The Reason Why Blaw-Knox Buckets OUTDIG



The WHY of digging power in a Blaw-Knox Bucket is easy to understand.

1st—The preponderance of weight is in the scoops, where it belongs.

2nd—Blaw-Knox Buckets close easily, requiring less pull on the closing line due to (a) elimination of friction through the use of ball bear-

> ings (b) greater cable overhaulage with but few sheaves.

> 3rd—Blaw-Knox Buckets penetrate easily because they are equipped with sharp cutting lips which are tempered to resist abrasion.

> After you use an improved Blaw-Knox Dreadnaught Bucket, you will revise your opinion as to how small an item bucket maintenance can become.

#### BLAW-KNOX COMPANY

2086 Farmers Bank Building, Pittsburgh, Pa.

New York
Chicago Birmingham Detroit
Boston Buffalo Baltimore

Export Division: Canadian Pacific Bldg., New York, N. Y.—London-England, New Oxford House, Hart St., Holborn, W. C. I.—Paris. France, I Rue De Clichy—Milano, Italy, 6 Via S.Agnese, 6

### BLAWNOX


The Wagon Grader a self contained dirt moving unit that



2 8's Farmers Bank Bldg., Pittsburgh, Pa. Send me complete information on Ball Wagon Grader 
Clamshell Buckets 
Dragline Buckets

STRUCTURAL STEEL CREATED THE SKYSCRAPER

#### DREAMS THAT WILL LIVE IN STEEL



AN ENLARGEMENT OF THIS HUGH FERRISS RENDERING, ON SPECIAL STOCK FOR FRAMING, WILL BE MAILED WITHOUT CHARGE TO ANY ARCHITECT, ENGINEER, OR BUSINESS EXECUTIVE.

How HIGH the new city holds its head! The vaulting arch . . . the arrogant spire . . . the clean-limbed river span . . . these safely dare to reach so far because steel is in their veins.

Versatile steel! Worker of miracles solely through proved engineering formulæ and the competent art of drafting boards! For steel's adaptability, steel's strength and security are definitely known—controlled by scientific test and analysis at every stage in its manufacture.

Structural steel brings speed, safety and economy to the erection of small as well as large structures—to homes, apartment and mercantile houses, schools and small bridges. Before building anything find out what steel can do for you. The Institute serves as a clearing house for technical and economic information on structural steel, and offers full and free co-operation in the use of such data to architects, engineers and all others interested.

The co-operative non-profit service organization of the structural steel industry of North America. Through its extensive test and research program, the Institute aims to establish the full facts regarding steel in relation to every type of construction. The Institute's many publications, covering every



phase of steel construction, are available on request. Please address all inquiries to 200 Madison Avenue, New York City. District offices in New York, Worcester, Philadelphia, Birmingham, Cleveland, Chicago, Milwaukee, St. Louis, Topeka, Dallas and San Francisco.

#### AMERICAN INSTITUTE OF STEEL CONSTRUCTION

STEEL INSURES STRENGTH AND SECURITY

#### **SMOOTHER**

### POWER


#### THAT'S WHAT YOU WANT

MOOTHER POWER . . . vibrationless power bespeaks
LeRoi Engine quality . . . quality in design and materials.
So completely has this quality been apparent to its worldwide users, that they are now using LeRoi gasoline engines
in the "toughest" of heavy duty service of manifold variety.

And LeRoi's performance bears out its staunch build . . . in road-building . . . in logging . . . in dirt-moving and hundreds of other applications. Its efficiency is told in its low operating costs . . . its ability to provide "full-measure" power under capacity load . . . and its long years of faultless service.

Those using the LeRoi Engine know of its flexibility, of its smooth acceleration and of its low upkeep costs. You can look to the LeRoi for Dependable Power . . . always!

LE ROI COMPANY, Milwaukee, Wisconsin



E ROI ENGINES

FOR DEPENDABLE POWER



### The LOADMASTER SWING-CRANE

LIFTS . . . . SWINGS . . . . CARRIES . . . . HAULS

THIS crane has been designed to operate easily and efficiently under congested conditions. Its pactness allows of maneuvering in confined space, its mobility affords quick transportation, its mode of operation, with swinging boom and without the use of stifflegs, means facility in handling of loads.



BEING sturdy, mobile and easy to manipulate, the LOADMASTER is especially adapted for use by public utilities, railroads, municipalities, contractors; for operating on piers, in terminals and in crowded thoroughfares. The facilities it offers are never so fully appreciated as when congestion is


#### FREDERIC H. POOR, Inc.

LOADMASTER SWING-CRANE 342 Madison Avenue New York, N. Y.

Send for Catalog

LOADMASTER SWING-CRANE

#### NO-PRESSURE WATER TANK—



### MULTI FOOTE PAVER

for Speed-Service-Success

For 1930 Equipment MultiFoote has created a New, No-Pressure Water Tank.

The Measuring Tank, the accuracy of which is not affected by water pressure, condition of grade or air in the supply line, is filled from an open top Auxiliary Supply Tank controlled by a Float valve.

This Equipment relieves the operating valves from that constant wear resulting from operating under pressure. MultiFoote offers to the paving contractor an advanced improvement which will be evident as each day's yardage is completed.

TIMKEN BEARINGS HERCULES HEAVY DUTY GASOLINE MOTORS

THE FOOTE CO., Inc.
Nunda, N. Y.

DISTRIBUTORS
THE HUBBARD-FLOW FOR CITY
MULTIFOOTE SALES CO.
2811 W. Fulton Street, Chicago, Illinois
WILCON BROS.
588 Chenargo Street, Blinghamton, N. Y.
BURYON FRANKLIN COMPANY
MEMBERSHAM CO. O.
7 DIOMON FANKLIN COMPANY
MEMBERSHAM CO. O. T.
DIOMON FANKLIN COMPANY
MEMBERSHAM CO. O. T.
DIOMON FOR THE PROPERTY CO.
555 Thurman Street, Portland, Oregon
C. H. JONES COMPANY
134 Pierpont Av. Salt Lake City, Utah
LONDON CONCENST, BLICHINGRY CO.
LONDON, OWNERST, BLICHINGRY CO.
LONDON, OWNERST, BLICHINGRY CO.

World's Largest Exclusive Builders of Road Pavers

#### In Old SPAIN . . and PORTUGAL too



COLAS modernizes ancient highways


HESE roads, constructed long ago at immense cost and labor when Spain and Portugal were at the height of their power, are now being rebuilt and modernized, simply and economically, with Colas. This cold asphalt road emulsion has met with such remarkable success that wherever used the name Colas has become synonymous with Good Roads. Its ability to withstand unusual stress in traffic and weather conditions with efficiency unimpaired warrants its use everywhere. If you are interested in road construction or maintenance, you should know about Colas. Write for specifications and literature.

#### FLINTKOTE ROADS INC.


(COLAS LICENSEES)

Persbing Square Building, New York Park Square Building, Boston Associated Companies Throughout the World





Largest wire rope manufacturers in the world



American Wire Rope for the excavating machines and for the hoists. American Wire Rope for the elevators—and for any other purpose where a reliable wire rope is required. As a part of Construction equipment, as a part of Elevator Service, American Wire Rope has proved its advantages. Every foot is tested before it is shipped. This means much to your advantage as it results in increased service and lower operating costs. Specify American Wire Rope for your severe service requirements.

#### AMERICAN STEEL & WIRE COMPANY

SUBSIDIARY CUNITED STATES STEEL CORPORATION

30 Church Street, New York

Other Sales Offices: Atlanta Baltimore Birmingham Boston Buffalo Cincinnati Cleveland Dallas
Denver Detroit Kansas City Memphis Milwaukee Minneapolis-St. Paul Oklahoma City Philadelphia
Pittsburgh Salt Lake City St. Louis Wilkes-Barre Worcester

U. S. Steel Products Co.: San Francisco Los Angeles Portland Seattle Honolulu Export Distributors: United States Steel Products Co., 30 Church St., New York City

FROM GROUND-LINE . . . TO SKY-LINE

### Sterling




WHEELBARROWS

and CONCRETE CARTS

were used in large quantities by the W.T. GRANGE CON-STRUCTION COMPANY of PITTSBURGH, in the erection of the new William Penn Hotel.

They are old customers of Sterling Equipment, having standardized on both Sterling Wheelbarrows and Concrete Carts on all their jobs.

The Grange Company is one of the oldest and most reliable Contractors in Pittsburgh, which speaks for Sterling's accepted higher efficiency in contributing to Lowered Operating Costs.



STERLING ON A WHEELBARROW MEANS MORE THAN STERLING ON SILVER ANY

BRANCH WAREHOUSES-BOSTON, NEW YORK, PHILADELPHIA, PITTSBURGH, CLEVELAND, DETROIT, CHICAGO, ST. LOUIS



A high-early-strength concrete patch, made according to Univer:al Atlas tested methods, restored this 36-inch water main to use in less than a day.

#### Back Into Service In Less Than a Day

Patching a 7-inch hole in a water main with high-early-strength concrete enabled the West Virginia Water Service Co., Charleston, W. Va., to put the main back into service in less than a day. The concrete was made according to Universal Atlas tested methods; standard portland cement of the Universal Atlas company (the same as furnished for regular work) was used. A. L. Johnston, engineer; Henry Clay, superintendent, both of the water service company.

The hole was in a 36-inch pipe connecting a settling basin with the filters. It was first caulked with tar and lead wool, then bound with a wide ½-inch steel band. Forms were placed around the pipe to insure a minimum concrete thickness of 18 inches. The concrete was placed at a temperature of 65° F. and was kept at that temperature with a salamander. Proper curing moisture was maintained by sprinkling.

Methods for obtaining high-early-strength concrete with the standard portland cement furnished by the Universal Atlas company will be sent on request. Just use the coupon.

#### Universal Atlas Cement Co.

Subsidiary of United States Steel Corporation

Concrete for Permanence

By carefully following Universal Atlas methods you obtain not only high-early-strength but denser, more durable concrete as well.

Universal Atlas Cement C 208 South La Salle Stre	
	send me methods for securing high-early- te with the standard portland cement of the o.
Name	
Address	
City	State —
C.M. 5-30	Convright Univ

PRODUCTS: Atlas Portland Cement, Universal Portland Cement Atlas White Portland Cement, Atlas Lumnite Cement

PLANTS AT Hudson, N. Y., Northampton, Pa., Universal, Pa., Buffington. Ind., Duluth, Minn., Hannibal, Mo., Independence, Kan., Leeds, Ala., and Waco, Tex.

OFFICES IN Chicago, New York, Philadelphia, Boston, Albany, Pittsburgh, Cleveland, Columbus, Minneapolis, Duluth, St. Louis, Kansas City, Des Moines, Omaha, Oklahoma City, Birmingham and Waco

Copyright Universal Atlas Cement Co., 1930

### Construction Methods


A McGraw-Hill Publication-Established 1919

ROBERT K. TOMLIN, Editor

VOLUME 12

NEW YORK, MAY, 1930

NUMBER 5





VERTICAL BOOM DITCHER (above) averages about 3,600 ft. of trench per 12-hr. day at Sky Harbor Airport, Chicago, where 70,000 lin.ft. of tile was laid. At Steinberg Airport (below) the average was 3,500 ft. per 8-hr. day.

Vertical Boom Ditcher Digs Trench for

#### AIRPORT DRAINAGE

THE drainage problem at the recently constructed Steinberg airport in St. Louis was met adequately by laying 30 miles of tile of which 138,000 ft. was of 6-in. size and the remainder of 8-, 10-, 12-, and 15-in. sizes. A Barber-Greene ditcher, owned by H. J. Fauber of Marion, Ill., dug most of the trench for this tile. A machine of the same type handled the trenching for 70,000 lin.ft. of tile at Sky Harbor airport near Chicago.

On the Steinberg job two 3-ton vertical digging booms, making 9-and 21-in, cuts were used on the machine. Changes were made in the field from one boom to the


other, without the aid of rigging, by allowing the booms to dig halfway in to the ground and thus support themselves until the necessary bolting and unbolting of push arms was accomplished.

arms was accomplished.


Targets 8 ft. high were set at frequent intervals along the ditch line. By sighting on these targets the operator was able to keep the trench to grade without leaving his seat, the power boom hoist on the machine governing the depth of the trench.


With the narrow boom the machine digs at the rate of 3,500 ft. per 8-hr. day with a maximum in four hours of 2,065 ft. and a maximum in 7 hours of 3,650 ft.

#### This Month's "News Reel"



DIABLO DAM on Skagit River, constant-angle concrete arch structure 386 ft. high, is important unit in power development program of Seattle, Wash. Winston Bros. Co., of Minneapolis, used belt conveyors to distribute the concrete in the dam.





STEEL ARCH for new interstate bridge reaches out over the Kill van Kull to connect Port Richmond, Staten Island, N. Y., with Bayonne, N. J. Main arch, 1,675 ft. long, is being erected by the American Bridge Co., using steel falsework towers.

HUGE GATES (above) in place at one of the seven locks of Canada's Welland ship canal, connecting Lakes Erie and Ontario by a 25-mile route. The locks are each 820 ft. long and 80 ft. wide, with a lift of 46½ ft. Total lift between waters of two lakes is 325½ ft. Lock gate heights range from 35 to 83 ft. Each gate leaf consists of horizontal steel girders inclosed on both sides by steel sheathing sheets. sheathing sheets.



ELEVATED EXPRESS HIGHWAY is under construction by James Stewart & Co., Inc., along Hudson River to carry vehicular traffic between Canal and 72nd Sts., New York.



AFTER SIGNING federal-aid highway bill April 4. President Hoover and members of congressional roads committee increase federal aid from \$75,000,000 to \$125,000,000 per year



ANOTHER CHICAGO SKYSCRAPER, the La Salle-Wacker building, rears its head 40 stories above Wacker Drive.

DEDICATED. (below)
Wanaque dam and 20-mile
steel pipe aqueduct are officially placed in service to
supply 100,000,000 gal. of
water daily to ten New Jersey communities.



CONSTRUCTION METHODS-May, 1930


of hip by ft. ft. is

ntal teel

DS

@ Keyston





#### By VINCENT B. SMITH

Assistant Editor, Construction Methods

CONDITIONS approximating those encountered in pioneer rail-road construction of 40 years ago have called forth all the skill and resourcefulness of the engineers and contractors who are building the 28.1-mile line of the Nicholas, Fayette & Greenbrier Railroad in the canyons of the Gauley and Meadow rivers, between the villages of Swiss and Nallen, W. Va. In spite of the remoteness of the project and the difficulty of construction in the steep and narrow canyons, modern methods and machines are enabling the builders to make rapid

The Nicholas, Fayette & Greenbrier Railroad, named for the three counties which it traverses, is a corporation controlled by the Chesapeake and Ohio and the New York Central and authorized by order of the Interstate Commerce Commission to give both the competing railroad companies economical access to virgin coal and timber land. Under the contract between the controlling companies, it is provided



PROJECTED GRADE LINE, approximately 55 ft. above Meadow River, penetrates solid rock bluff, requiring cut 120 ft. high to top of slope.

### Beginning a Series Railroad Construction

Modern Machines and of 28-Mile Link

that the Nicholas, Fayette & Greenbrier Railroad will assume ownership of a 40-mile branch, title to which is now in the Chesapeake and Ohio, extending from the main line at Meadow Creek to Nallen, and of several feeders tributary to this branch, all known as the Sewell Valley subdivision and embracing the railroads of the

G. N. WRIGHT (left) and J. W. MURPHY, of Brown, Murphy & Wright, sub-contractors for 3t miles of grading.

Loop and Lookout, Sewell Valley, and Greenbrier and Eastern companies. The 28.1-mile line under construction really is a connection between the southern terminus of the Ohio Central Lines of the New York Central Railroad at Swiss, 47 miles east of Charleston, W. Va., and the terminus of the existing Sewell Valley subdivision at Nallen.

Grades up to 3½ per cent and four switchbacks on the line made the Sewell Valley subdivision from Meadow Creek to Nallen expensive to operate. The new line gives access to the same territory over maximum grades of 2 per cent, compensated, and maximum curves of 11½ deg. There are no grades against loaded traffic. By building a short connection at Beech Glen, approximately 2 miles below Swiss, the Chesapeake and Ohio gains access to the new line at the north end over the tracks of the New York Central.

Difficulties of Country—The rugged character of the terrain greatly increases the difficulties of transportation and construction. This portion of the Appalachian Range probably is as rough as any part of the United States. Along many parts of the line, the canyon walls rise from the Gauley and Meadow rivers at angles of 45, 60, and 90 deg. to heights of 400 or



NORTH PORTAL of Koontz Bend tunnel looks out on piers of Gauley River bridge. Horses and mules haul heading muck to portal.

# of Articles on in Mountain Country-I

Methods Speed Building in West Virginia

es

ik

d

le

al

IS

0

d

500 ft. A typical canyon wall might be described as a talus slope lying on a 1:1 or steeper slope from the water's edge to a height of perhaps 200 ft., where the slope ends in sheer sandstone cliffs. These talus slopes were covered by an almost impenetrable growth of virgin timber, laurel, and underbrush, through which the engineers of several surveys made by different railroads in the past 25 years with great difficulty projected their preliminary lines.

The steepness of the slopes and the tortuous windings, combined with the rapid fall, of the streams made satisfactory location difficult. A few relocations of the original line have been made by C. M. McVay, engineer of construction, with the aid of the engineers assisting him, to improve the alignment or reduce construction costs. Approximately 60 per cent of the line is on curves, the maximum curves being one of 9 deg. on the Gauley River and three of 11½ deg. on the Meadow River.

Two tunnels and one large bridge are included in the line. Tunnel No. 1, at Koontz Bend, is 3,200 ft. long; tunnel No. 2, at Carnifex Ferry, is 900 ft. in length. The only large bridge, crossing the Gauley River just below the mouth of Peter's Creek, 8½ miles above Swiss, is a 710-ft. plate girder


structure, consisting of eight 80-ft. spans and one 70-ft. span. There are six small deck girder bridges, spans 15 to 44 ft., and ten arch and box culverts, 10- to 20-ft. openings on the line.

Construction Quantities and Progress—Excavation amounts to approximately 1,500,000 yd., more than half of it solid rock. About 15,000 yd. of

O-ft. RUGGED TOPOGRAPHY increases difficulties of construction. Koontz

RUGGED TOPOGRAPHY increases difficulties of construction. Koontz Bend tunnel pierces mountain in foreground. Compressor plant and mixing plant are on far side of Gauley River.

concrete are required for the bridges and drainage structures. Because of the inaccessibility of the projects, all coarse and fine aggregates are crushed



IN CHARGE OF CONSTRUCTION. (Left to right) C. M. FAULKNER, superintendent, A. Guthrie & Co., Inc.; J. A. STOCKER, chief engineer, Ohio Central Lines; G. S. PLUMLEY, resident engineer on Residency 1; and C. M. McVAY, engineer of construction.

from hard local sandstone at the sites of the structures.

A. Guthrie & Co., Inc., St. Paul, Minn., was awarded the contract on February 20, 1929. The contract stipulates a completion date of July 1, 1930. Excavation of the tunnel benches, lining of the tunnels with concrete, and track laying were the only major operations still to be performed on Feb. 1. At that time grading was more than 90 per cent complete, and masonry was 98 per cent complete.

Access to Project—The job was accessible at five points, as indicated on the map. From Swiss, an old standard-gage lumber railroad ran up the Gauley to Peter's Creek (the location of the bridge and long tunnel) and thence up Peter's Creek, meeting a state road at Lockwood, 3 miles from the Gauley River. This railroad offered two means of access, one from Swiss and one from Lockwood. However, the track was serviceable only for a short distance out of Swiss, as the rest of the line had been abandoned 11 years before.

Two rough, narrow, unimproved county roads offered the very difficult but only available means of transporting equipment and materials to the sections of the line between the long tunnel and Shawver's Bridge. These two roads are shown on the map as the Saturday Road and the Sunday Road. At the south end of the line,



G. S. PLUMLEY (left), resident engineer, and A. B. CHURCHILL, masonry inspector, on Residency 1, in Mr. Churchill's camp at Peter's Creek.

a narrow-gage railroad extended from Nallen for approximately 6 miles down the Meadow River. This railroad, being located on the proposed right-of-way of the N. F. & G., on the south side of the river, had to be moved to a former location on the north side. A bridge to accommodate this relocation was built across the Meadow River about 1½ miles above Shawver's Bridge.

Engineering Supervision—By agreement between the two owners of the N. F. & G., construction has been

placed under the supervision of the New York Central, with J. A. Stocker, chief engineer, Ohio Central Lines, Columbus, Ohio, in charge. Operating under Mr. Stocker at Charleston, W. Va., is Mr. McVay, engineer of con-



W. L. PIPER, of Piper & East, and J. E. HAMMOND, resident engineer on Residency 2.

struction, assisted by G. L. Link, assistant engineer of construction (of the Chesapeake & Ohio). The line is divided into three residencies. Residency 1, extending 10 miles up the river from Swiss and including the bridge and Koontz Bend tunnel, is supervised by G. S. Plumley, resident engineer. Residency 2, 8 miles in length, takes in some of the heaviest grading on the line. J. E. Hammond, resident engineer, is in charge of this section. Residency 3, 10 miles long, including the 900-ft Carnifex tunnel and the grading work to Nallen, is under the control of W. H. Eary.

Sub-Contractors-A. Guthrie & Co.. Inc., sublet most of the work to five contractors, reserving for itself the long tunnel, the bridge, and 2½ miles of heavy grading, below Shawver's Bridge. A. Keathly, Charleston, W. Va., is doing the grading and track laying on the 8 miles from Swiss to Peter's Creek. G. A. Rosenbaum, East Bank, W. Va., has the approach cut at the south portal of the Koontz Bend tunnel and 1 mile of grading work beyond. Piper & East, and Brown, Murphy & Wright, of Princeton, W. Va., assumed a sub-contract to grade the next 7 miles. Dempster Construction Company, Knoxville, Tenn., is doing the work on the next 14-mile section, including the driving of the 900-ft. tunnel. The 2½-mile grading section of A. Guthrie & Co.,



DIESEL SHOVEL crashes through forest to site of arch culvert.



STONE CULVERT on Brown, Murphy & Wright's section. Project includes half dozen of these native stone culverts.



LOCATION MAP of Nicholas, Fayette & Greenbrier Railroad. New construction connects southern terminus of New York Central with Nallen terminus of Chesapeake & Ohio's Sewell Valley subdivision.



ACCESS TO NEW CONSTRUCTION is possible at five points: Swiss, Peter's Creek railroad, Saturday Road, Sunday Road, and Nallen. Figures along route indicate mile posts.

Inc., intervenes between the Dempster Construction Company and the 8-mile grading section of Poston, Brewer & Brewer, Chillicothe, Ohio, extending from near Shawver's Bridge to Nallen.

General Construction Plan — The critical factor in the completion of the railroad by scheduled date is the long tunnel. To expedite construction of the tunnel, par-

ticularly of the lining, it is desirable, if not necessary, that the bridge be completed to afford a secure crossing for

concrete trains. No site for a crushing and concrete plant was available on the tunnel side of the river and the plant was placed on the north side to serve both bridge and tunnel. To get in bridge steel from Swiss, track must be laid as far as Peter's Creek.

While concrete lining of the Koontz Bend tunnel is being completed, it is expected that




ALEXANDER HOLMAN (above), superintendent for A. Keathly, makes use of one sure means of transportation in rough country.

D. R. PHILLIPS (left), inspector, and W. J. LEWIS, superintendent, are in charge at south portal of Koontz Bend tunnel.

LON HAWK (left), superintendent for Poston, Brewer & Brewer, and W. H. EARY, resident engineer on Residency 3.





MILE 12 PARTLY CLEARED for grading, Piper & East section. Grade line is about 40 ft. above Meadow River.

track can be laid from Nallen through the lined short tunnel to the south portal of the long tunnel. Rail heads can then meet in the long tunnel in time to have the railroad ready to operate July 1. Construction operations have been planned to meet this schedule.

Methods of Construction—The purposes of this article can be well served by considering the methods employed on the different contract sections in order, starting with the zero mile post at Swiss.

A. Keathly Sub-Contract Section— Total excavation on the 8 miles between Swiss and the north end of the bridge amounts to 400,000 yd., of which 50 per cent is hard rock and 20 per cent, loose rock. Practically all excavation is in sidehill cuts on slopes ranging from 1:1 to cliffs. Cuts vary from 20 to 100 ft. deep, measured to top of slope.

About 60 per cent of the material is cast. Trucks hired on contract do most of the hauling. On the first mile, however, where the lumber company track was in good condition, a Bucyrus 70 2½-yd. track-type railroad shovel loaded two 20-yd. Western airdump cars. A Vulcan standard-gage saddle-tank steam dinkey hauled about 40,000 yd. of spoil in these cars a distance of ½ mile. While the railroad shovel was loading on this section, a Lorain 11-yd. gasoline shovel went ahead another mile, side casting. From Mile Post 2 to Mile Post 4, this shovel and another Lorain 11-yd. cast and loaded material. Here the Bucyrus 70 again was brought up with great effort to cast for 1½ miles. The Lorains excavated all the earth and rock on the last 3½ miles. Two ½-yd. steam Eries follow the 14-yd. excavators to trim and finish the grade.

Wherever practicable on the Keathly section, a Sanderson Cyclone 6-in. gasoline well drill was used to put down the holes for blasting. As all the spoil was needed for fills, great care was taken in loading the holes to break the rock without wasting it into the river. Alexander Holman, superintendent for Mr. Keathly, drilled the holes to grade on the ditch line and loaded them with Judson powder, a low-strength, slow-acting high explosive in granular form. The holes ranged up to 60 ft. in depth.

A few experiences in which rock failed to break to grade in blasting showed the necessity of drilling the holes again after springing to be sure they were open to the bottom. When holes were loaded to the bottom, the blasts were very successful, breaking the sandstone, which here is stratified in thick horizontal layers, to grade,

without dislodging the material more than a couple of feet.

In many places it was impossible to perch the well drill on the edge of the cliffs. At these points, portable compressors and jackhammers were employed to break down the face of the rock in steps. One 80-ft. cliff was blasted in this way, the jackhammers drilling 16-ft. holes, and 4-ft. benches being left between lifts to form a \frac{1}{4}:1 slope.

A. Keathly laid the track on his section, using a Bucyrus locomotive crane for this work. The New York Central is supplying 105-lb. rails from its main lines, where this weight is being replaced by the new 127-lb. standard. Track was laid to Peter's Creek early in March, as desired by the general contractor to permit delivery of bridge steel.

Peter's Creek Railroad - To hau! equipment and materials to the mouth of Peter's Creek, the contractor rebuilt the railroad from Lockwood, converting the standard-gage to 3-ft. gage and building six trestles up to 310 ft. long across Peter's Creek. For stringers on these trestles and on the construction bridge across the Gauley River at the mouth of Peter's Creek. the contractor used 56-lb. rail from the lumber company track taken up between Peter's Creek and Swiss. Bents of the Peter's Creek trestles rest on rock-filled cribs and on wood sills. A 20-ton Plymouth gasoline locomotive operates over the narrow-gage track from Lockwood.

NEXT MONTH: The second article of this series will describe methods of bridge construction, tunnel driving, and grading.



CONCRETE ARCH CULVERT, with heavy bench walls and relatively thin arch ring, and dump trestle for 48-ft. fill on general contractor's grading section.




# Fourth Design Prize Won by CIRCULAR AIRPORT

HOURTH PRIZE of \$500 in the Lehigh Airports Competition, sponsored by the Lehigh Portland Cement Co., was awarded to Will Rice Amon, architect of New York City, for his design of a modern airport to serve a typical American city.

The designer has adopted a circular flying field with parallel runways crossing the field in four directions and separating incoming and departing planes. A modernistic main terminal building, with covered wings for loading and unloading passengers, is placed at the

edge of the field facing a plaza surrounded by stores, shops, a hotel and other structures serving the needs of a busy airport.

First, second and third prize designs were shown in the February, March and April issues.



#### Ninety Gas-Engine Driven

## Mexico's First Arc-



GASOLINE for the ninety welding machines is supplied from these tanks mounted on a truck which travels along the pipe line route and makes refueling a convenient process.

Contractor Prepares
165-Mile Route for
Transportation of
Natural Gas From
Texas to Mexico

perienced laborers to do the welding as well as to operate the excavating machinery. Construction was started from both the United States and the Mexican sides of the Rio Grande, the two gangs working toward each other.

Welding Operations—In the construction of this line, as is customary on all pipe lines fabricated by the arcwelding process, the pipe was distributed along the right-of-way and lined

INETY gas-engine driven welding machines were mobilized into service by Smith Brothers, Inc., general contractors of Dallas, Tex., for the construction of Mexico's first arcwelded pipe line recently completed for the Compania Mexana de Gas, a subsidiary of the United Gas Co. This new 12-in. natural gas pipe line, 165 miles long, runs from Aquilares to Roma, Texas, then across the Rio Grande River, via the International Bridge to San Pedro, Mexico, and thence to Monterey, Mexico.

Difficulties—The difficulties experienced in the construction of this Mexican line were many and varied. It was laid over mountains, through primitive forest and across rivers. Most of the labor used was inexperienced because of the Mexican law



BURROS transport Mexican laborers to and from the pipe-welding job.

which required that most of the work be done by native residents of the state in which the work is going on. It was necessary to train these inex-


up in sections ahead of the firing-line welders by crawler tractors equipped with crane boom attachments. These sections are composed of from 6 to 8



REGIMENT OF MA-CHINES mobilized and awaiting travel orders to various locations where they will provide current for pipe-welding operations.

#### Machines Supply Current for

## Welded Pipe Line



welders was supplied from a truck as shown. Some idea of the welding equipment used in the construction of this line may be gained from the photograph at the bottom of the opposite page which shows the line-up of welding machines ready to be moved into place along the route. The electrodes or welding wire used in welding the joints was of  $\frac{3}{16}$ -in. diameter. All of the welding machines and electrodes used in the construction of this line were manufactured by the Lincoln Electric Co. of Cleveland, Ohio.

Installed largely by Mexican labor, as required by Mexican law, the Aquilares-Monterey 12-in. arc-welded pipe line is the first of its type to carry natural gas in Old Mexico.

FIRING-LINE WELD (below) is made by native operater who then proceeds to make burning-in and finished welds

lengths of pipe, lined up on skids and tack welded by the welding operator assigned to the section. After the tack welds have been applied to a complete section, the welder returns to the first joint and applies the burning-in bead half way around the circumference. The pipe then is turned and the remaining half is welded. The operator's helper follows him across the section, cleaning the burning-in weld in preparation for the finished weld. While the finished weld is being applied the helper turns the pipe so that the finished weld may be completed in one continuous operation. A Mexican operator making a firing-line weld is shown in one of the photographs.

ing ted the the er. onary rctrined

ese

DDS

As the sections are completed they are placed over the trench on skids and the tie-in welds are made by the bell-hole gangs. In making these connections the weld must progress around the pipe as it remains stationary because it is impossible to turn the entire line.

Of the 90 welding machines which supplied the current for welding, 48 were used on the portion of the line in the United States and 42 on the Mexican portion. The welders were moved into position along the line by Caterpillar tractors. Gasoline fuel for these



#### Boston & Maine Terminal Combines

#### RAILROAD STATION AND COLISEUM

Old Structure in Boston Wrecked and New One Built Without Halting Train Movements

THE financial experts of the Boston & Maine Railroad found that they could have a new North Station Terminal Building in Boston to replace the old station built in 1894, and at the same time increase the railroad revenue. This was made possible by including in the new building an up-to-date coliseum above the railroad station, and leasing it to the Boston Madison Square Garden. The increased rentals from this lease and from other concession spaces were more than sufficient to take care of the charges on the investment.

The station faces on Causeway St., between Haverhill and Nashua Sts., the dimensions being 440x205 ft.; the station facilities occupy the ground floor and mezzanine, with a total height of 22 ft. The station ceiling is applied to the underside of the heavy concrete slab which forms the floor of the coliseum. This is practically a duplicate of the Madison Square Garden in New York with a clear height to the trusses of 67 ft. and a seating capacity of 18,000.

In laying out the construction, primary consideration was given to the continuous operation of the station, one of the busiest in the country, handling 360 trains a day, involving train movements during rush hours averaging 30 sec. apart. The old train shed was demolished by locomotive cranes working on the tracks between rush hours, and not more than two of the twenty-three terminal tracks were available for construction purposes at any one time.

Before wrecking the station building

By WALLACE E. BELCHER

Supervising Engineer, Dwight P. Robinson & Co., Inc.



PILEDRIVING was done with three rigs equipped with 65-ft. timber leads and 5,000-lb. steam hammers. New piles had to be located to miss old piles and other underground obstructions. Special caps were designed to fit each case. CONCOURSE PASSAGEWAY ROOF (in oval) was removed one section at a time to permit piledriver to enter from side.



COLISEUM FLOOR, convertible to hockey rink or boxing arena for 18,000 spectators, is a heavy concrete slab forming ceiling over railroad station below.

a temporary concourse of timber construction was built in the old concourse, and above this the wrecking and later the new construction work was carried on. For passengers crossing the 100-ft. space between the concourse and Causeway St. covered passageways were built, and shifted back and forth as the work progressed.


Foundation Work Difficult—The driving of piles under the concourse area was accomplished by removing one section of the roof at a time so


that the driver could enter from the side far enough to place the piles. The foundation work was difficult, as the old footings were all heavy granite blocks on closely driven wood piles and the foundations of former buildings and dock walls were much in evidence. A greater quantity of old rock was taken out than the quantity of earth excavated. Neither the piles nor the sheet piling could be driven through the old rubble work, nor could any of the old piles be pulled, although pulls

of about 60 tons were applied, which resulted only in breaking up the piles or breaking the rigging. The new piles were consequently driven to miss the obstructions as near to the desired location as possible, and special caps designed to fit each case.

Pile-driving was done with 5,000-lb. Vulcan steam hammers to a penetration of eight blows per inch, Simplex poured-in-place concrete piles being used. Concrete for foundations and piles was handled by special buckets, moved on industrial track. The New England Foundation Co. used three pile-drivers with 65-ft. timber leads, equipped with 9x10-in. Lambert hoisting engines.

Concreting Plant-The size of the





ROOF TRUSS ERECTION is handled by 25-ton guy derricks with 125-ft. masts and 116-ft. booms. Main trusses, assembled in upright position and raised to tops of columns, have span of 175 ft. and weigh 40 tons each.

HODS.


superstructure and the requirement of 15,000 cu.yd. of concrete dictated the use of a central concrete mixing plant and high tower for gravity distribution. A 20-ft. platform between two passenger tracks was developed as a concrete plant, sand from one track and gravel from the other being received and placed in bucket elevators and storage bins. A Blaw-Knox 72-ton steel bin, and batch-measuring outfit were used, delivering to a 1-yd. Ransome mixer, and thence to the tower skip. The rate of capacity of the plant was 40 cu.yd. per hour and the biggest day's run 700 cu.yd. when pouring the triple ramp at either end of the structure.

The limited storage space available at the job for handling mortar materials and the fact that an ample supply of ready-mixed mortar could be purchased for delivery as wanted led to the use of Blue Diamond mixed mortar delivered by truck. The brick hoists were placed in locations just outside the building walls, convenient for truck deliveries, not only of mason material but also for miscellaneous materials of all kinds.

Steel Erection-Steel erection was carried on by the George F. Watts Co. in two sections, the lower portion amounting to 1200 tons being erected by a stiff-leg derrick with 105-ft. boom, moving along the station roof deck as it was built. On this deck two 25-ton guy derricks with 125-ft. masts and 116-ft. booms were set up for erecting

the 2600-ton coliseum superstructure. The main trusses, spanning 175 ft. and weighing about 40 tons each, were composed of rolled beam sections shipped knocked down. These were assembled in an upright position on the deck, directly under their final position. They were then hoisted vertically by the two derricks and set into the tops of the main columns. This reduced the amount of riveting aloft to a minimum. Roof details were set by two 3-ton jinniwinks on the roof level.

All the steel was painted before the roof slab was placed, thus avoiding the erection of special scaffolding for painters which would have been extremely expensive for this height of



STEELWORK called for the placing of 3,800 tons. Roof details were placed by two 3-ton jinniwinks. TRUSSES (in oval) were raised to place as units, after they had been completely assembled on the ground, thus reducing riveting aloft.

the flanges of the tees Acoustex sound-absorbing slabs were laid, which were 2x6 ft. in size and 1-in. thick. This formed the permanent underside of the gypsum slab and at the same time assured perfect acoustic properties for the arena. It is doubtful if wooden forms could have been erected as cheaply as the Acoustex material, which cost about 22 cents per square foot in place.

Fireproofing of the heavy girders was a large item and the amount of form work required had to be kept down to a minimum, both on account of the time available as well as the cost. This fireproofing was accomplished by casting a gypsum shoe around the lower

2

CC

New York. Dwight P. Robinson & Co., Inc., were the designing engineers and constructors.

NEXT MONTH: Building the Salt

game being played Nov. 20, 1928.

with a capacity audience, the first ice hockey

The work was under the direction of W. J.

Backes, chief engineer, and F. C. Shepherd,

consulting engineer of the Boston & Maine Railroad. The architects were Funk & Wil-

cox of Boston and Fellheimer & Wagner of

California, a rock-fill structure of 3,000,000 cu.yd. involving large scale quarrying operations by the Pacific Gas & Electric Company.

Springs dam on the Mokelumne River,

FIERS OF SEATS (above) were installed in the coliseum portion of the dual purpose structure after the steelwork had been erected and riveted.

ture.

. and

were

tions

were n on

posi-

verti-

into This aloft

et by

level.

e the

ex-

r the

steel

d on

sorb-

size

nent

same

for

the

cents

as a

well

shed

ower

THODS

flange of the girder and following up by laying 3-in. fireproofing blocks on each side of the girder for the protection of the girder webs. This was later plastered with one rough coat to present a uniform appearance, with the exposed concrete work on the underside of the seat banks.

Such buildings usually require large areas of steel sash and the storage of the sash occupies considerable space. The sash is very likely to be damaged in rehandling and rough usage before it can be used. In this case early delivery of sash was avoided by the use of rolled steel subframes which were set into the masonry walls as they were built. This permitted the masonry work to be finished up as scaffolding was advanced and assured perfect fit for the sash when delivered.

The total cost of the work was \$3,500,000, all of which was completed without serious injury either to the public or to any of the employees, and without delay to train movements.

Demolition commenced Dec. 3, the station portion was put into use Aug. 20, and the coliseum opened Nov. 17



TAIL TOWERS AND CHUTES distributed concrete from a central mixing plant producing 40 cu.yd. per hour. For poured-in-place gypsum roof sound-absorbing slabs replaced wood forms.

CONSTRUCTION METHODS-May, 1930


## Getting Down to

DETAILS

Close-up Shots of Job Methods and Equipment


SUSPENDED (left) from cables stretched across canyon, two Byron-Jackson deep well pumps, with 6-ft. columns, driven by 75-hp. G. E. induction motors, unwater Owyhee dam site for General Construction Co. Winch on platform raises and lowers pump.

TUBULAR BOOM AND BUCKET ARM (below) feature Page 1-yd. hoe attachment on 75-hp. P&H excavator digging North Branch Canal on Kittitas Division of Bureau of Reclamation's Yakima Project.




CHICAGO BOOM ASSISTS DERRICK CAR in placing 69-ton girder, 122 ft. long, on Pigeon Creek viaduct of Pittsburgh & West Virginia Railway near Monongahela, Pa. Note brackets at front of derrick car to prevent overturning. McClintic-Marshall Co., contractor. Photo from G. A. CAFFALL, Manager of Erection, McClintic-Marshall Co.






GUY DERRICK carries concrete chuting system at San Antonio, Tex., sewage disposal plant. J. DePuy, San Antonio, general contractor. Photo from H. R. F. HELLAND, Associate Engineer, Hawley & Freese, Consulting Engineers.

GRADING DIALS enable rough grading crew to blade subgrade accurately. Madison Construction Co., Edwardsville, Ill., uses these dials at 50 ft. intervals to obtain close preliminary grading and cut down labor of fine grading. Hands are set to indicate whether grade is high or low and by how much.





REINFORCED JOINT (above) for submarine gas pipe facilitates construction and testing. Central Hudson Gas & Electric Corporation welds joints on barge by oxyacetylene process and lowers pipe to bottom of Hudson River as barge moves ahead. Linde compressed nitrogen takes place of air compressors in testing. Pressure of 350 lb. is applied to annular space between pipe and sleeve. Soap suds painted on sleeve welds indicate leaks at these welds. With sleeve welds tight, drop in pressure shows leak in butt weld.

STEEL-HULL WHIRLER-DERRICK BOAT built by Dravo Contracting Co., Pittsburgh, serves U. S. engineers on Mississippi River work in Memphis district. Steam-operated, full-revolving derrick handles 2-yd. clamshell bucket or 2-yd. drag scraper bucket on 75-ft. boom.

THODS

#### Road Builder Lays 91/2 Miles of Concrete from



# CENTRAL MIXING PLANT

CENTRAL MIXING PLANT (left). Tilting mixer discharges quickly. Conveyor delivers loose cement to hopper above mixer.

ONVINCED by its success in using a central mixing outfit for the construction of a concrete road at Marietta, Ohio, in 1928, that this type of plant was both practical and economical, the Dunzweiler Construction Co., of Zanesville, Ohio, last year applied the same method to the building of 9.48 miles of 9-7-9-in. pavement 18 ft. wide on U. S. Route 24 at Kentland, Ind. Equipped with a fast-discharging Smith 2-yd. tilting mixer and a fleet of ten Hug 4-ton trucks, the Indiana plant was capable

of laying 125 ft. of pavement an hour. This capacity was based on a mixing period of 2 minutes after all materials were in the drum.

The old fears of the paving contractor who hesitated to try central mixing, viz., that the trucks could not be dumped clean and that the concrete would be too stiff to yield the mortar for a good finish, were definitely dispelled by the Dunzweiler Construction Co. No admixture was used in the concrete, and the truck bodies were the standard end-dump

Hug 3-yd. size, with side corners rounded.

It was vitally important to have the consistency of the mix just right-a wet batch or one too dry caused trouble in getting the concrete out of the trucks; wet batches, also, had a tendency to segregate while in transit. Even on the longest haul of 6 miles, no serious separation of constituents in the mix occurred when the proper slump was used. An average slump of 1½ in. was sufficient. The experience of the contractor demonstrated that the wetness of the mix had to be regulated in conformity with the roughness of the haul, condition of the truck body, humidity, and atmospheric temperature. Of these four factors, the roughness of the haul was most important.

To keep the trucks on a smooth roadway and to save the subgrade from rutting, the contractor was more particular than on most truck jobs that the grade should be dry and solid before trucking would be allowed on it. Time lost in waiting for satisfactory subgrade conditions was regained by the speed of operations once work was resumed. Trucks were pneumatictired, with dual wheels on the rear axle.

The second important factor, condition of the truck body, was kept under control by a thorough nightly



FINISHING EQUIPMENT consists of two finishing machines and a belting machine. Hand floating is reduced to a minimum.



TRUCKS DUMP WET BATCHES on subgrade. Little concrete adheres to clean steel bodies. Consistency of mix is varied to conform with roughness of haul, condition of truck body, humidity, and atmospheric temperature.

cleaning which removed all adhering mortar from the steel and left the body smooth and shining for the next day's run. By keeping the subgrade smooth and hard and the bodies clean, concrete was hauled and dumped practically in the same condition in which it left the mixer.

ers

the

the

les, s in per of nce that gu-

uck

the

ad-

om

ar-

hat

be-

it.

ory

was

tic-

ear

on-

cept

htly

HODS

To put a perfect finish on the fairly stiff mix and to save time by eliminating excessive hand floating, the Dunzweiler Construction Co. used two Ord finishing machines and a Lakewood belting machine. After the two finishing machines had struck off the concrete, irregularities detected by checking with aluminum straight edges were removed by hand floating. The belting machine then finished the slab.

The central mixing plant was set up at the rock crushing plant of the Newton County Stone Co., about 3½ miles from the east end of the job. Crushed rock was obtained from the stone company, and sand and cement were shipped in, the latter being supplied by the state. The 2-yd. mixer and Blaw-Knox bins were erected on concrete foundations. A cement storage shed of 10,000-bbl. capacity was connected with the mixing plant by a Barber-Greene conveyor 80 ft. long. Cement handlers dumped the cement from sacks on to the conveyor, which delivered the material to a hopper over the mixer. Fourteen sacks went into the 2-yd. batch. Aggregates were weighed in Blaw-Knox batchers. A

Koehring gasoline crane with a 60-ft. boom handled sand and stone in a 1-yd. clamshell bucket.

An electrically powered Barnes triplex pump supplied the mixer with



G. L. BERRY (left), project engineer for Indiana State Highway Commission, and EARL MAXWELL, superintendent.

water. To guard against possible fluctuations in the power supply, a 1,000-gal. tank was placed on the mixing plant. Water was pumped to this reservoir through a 4-in. line, and the overflow was returned to a sump through a 2-in. pipe.

The specified mixing time for ordinary paving mixers in Indiana is 1 minute. Because of the unusual size of the mixer at the central plant, with the lower number of r.p.m., the engineers of the highway commission thought it advisable to increase the mixing period to 2 minutes, thus turning the batch over as many times as in the smaller mixers.


The results of beam tests showed higher early strength than beams broken on jobs where a central mixing plant was not used. This higher strength may be attributed to the longer mixing period. Beam tests showed no material difference in strength between batches which were in transit 30 minutes and those which were dumped 10 minutes after being mixed.

The contract section of the Dunz-weiler Construction Co. was 80 per cent old location. Rough grading, amounting to about 45,000 yd., was sublet. Paving started July 3 and ended Oct. 8. The longest day's run was 1,135 ft.; the average day's run, based on full working days for the season, was 865 ft. Progress was not above the average for 1-yd. pavers.


# DESCRIPTION TO THE !







STEEL CYLINDER to hold sand island is suspended from eight winch frames on falsework piles and is built up in 10-ft. rings. Diameter of shell is about 81 ft.



#### Step-by-Step


#### Using Sand Islands Construct Deep Piers of


SAND islands in steel shells were the solution for the deep pier construction problems encountered by Siems, Helmers & Schaffner, Inc., of St. Paul, Minn., on the Southern Pacific Suisun Bay bridge now under construction. Working in water up to a depth of 55 ft. above mud line and contending with strong tides having a maximum rise of about 7 ft., the locating and constructing of piers presented unusual difficulties. The maximum depth to bedrock below water is 143 ft., and earthquake possibilities require that the piers extend to bedrock.

The eight main piers are being built by the method illustrated in the accompanying photographs. The deepest pier will be




2 BEFORE LOWERING INTO WATER, (above) contractor completes fabrication of three rings, giving cylinder initial height of 30 ft.





May, 1930-CONSTRUCTION METHODS



WITH SHELL SUNK TO POSITION (left) derricks at some piers dredge out 10 ft. of mud. At other piers, no dredging is attempted before cylinder is filled with sand by clamshell buckets. Sand is obtained by dredging in bay nearby.

#### Field Methods

nds

of

deep

iems,

n the

ction.

and

about

usual

er is

piers


rated

11 be


#### in Steel Shells to Suisun Bay Bridge

approximately 214 ft. high, from bedrock to bridge seat, and will contain about 13,500 cu.yd. of concrete and 175 tons of reinforcing steel. Heavy reinforcing, amounting to 30 lb. per cubic yard of concrete, is used in the pier bases.

In the field, the work is in charge of H. I. Benjamin, assistant engineer of bridges, under the supervision of C. R. Harding, assistant to the president, and W. H. Kirkbride, engineer of maintenance-of-way and structures. C. M. Kurtz, office engineer on the job, provided the accompanying pictures. For the contractor, N. F. Helmers, vice-president of the firm, is in personal charge, with C. E. Ryan as general superintendent.



STEEL FORMS (above)
are erected on cutting
edge to make caisson
walls. Walls between
six dredging wells are 6
ft. thick.



ON SAND ISLAND INSIDE SHELL, (left) workmen erect cutting edge of 40x60-ft. caisson. Cutting edge is located accurately on dry, stable surface.

#### Step-by-Step Field Methods


(Continued)

## Using Sand Islands for



WHEN BEDROCK IS REACHED, divers inspect foundation conditions to see if cutting edge has penetrated hard shale.

SLIDING FORMS move up to permit pouring of 10-ft. lift containing 500 cu.yd. each day. After concrete has been placed to height of 25 ft., dredg-ing is started.




SKETCH of construction conditions and of contractor's scheme for sinking caisson through sand island inside steel shell.



S DREDGING WITH CLAMSHELL BUCKETS through six 10½x11½-ft. wells sinks caisson to bedrock at maximum depth of 143 ft. Dredging usually is done at night; 10-ft. concrete lift is added during day. By regulating dredging among different wells, caisson is kept plumb. As sinking progresses into stiffer blue clay, excavation sometimes extends to 5 or 6 ft. below cutting edge, and contractor resorts to dynamite to start caisson moving. Timber cofferdam is placed on concrete caisson above El.-20.


1 1 LOOKING DOWN INTO DREDGING WELL, (right) after 30-ft. seal has been placed and well has been unwatered. Rest of concrete is poured in dry.



1 () CONCRETE IS PLACED BY TREMIE (below) to seal dredging wells to height of 30 ft. above rock bottom.


divers see if hale.





12 ROUNDED-END PIER rests on caisson. This pier extends from El.-20 to 70 ft. above water.

FLOATING CON-CRETE PLANT pours caisson and pier. Plant includes 2-yd. mixer and 100ft. tower. Materials are delivered by barges.



Sixth of a series of articles on the \$325,000,000 construction program for flood control in the Mississippi Valley

# The Defense Against

## OLD MAN RIVER-VI

ARGE-CAPACITY machines for levee building in the Mississippi valley are represented by two outstanding, but radically different, types: the tower-cableway excavator and the long-boom dragline. Bucket sizes for the tower machines range from 5 to 10 cu.yd. and for the big draglines, with boom length as great as 150 ft., from 4 to 6 cu.yd. Both ma-

By ROBERT K. TOMLIN Editor of Construction Methods

Tower-Cableway Excavators and Large Draglines


Tower-Cableway Excavators-The tower-cableway excavator, in addition to its power plant, comprises four major elements: (1) A head-tower or structural steel frame extending to heights of from 70 to 100 ft. above ground and mounted on large double crawler tractions; (2) a tail-tower about 35 ft. high, also on crawlers; (3) a wire rope track cable spanning the borrow pit between head-tower and tail-tower; (4) a digging bucket of from 5 to 10 yd. capacity, carried out on the track cable and hauled in by a drag cable from the head-tower. While tower machines place the bulk of the fill directly within the limits of the levee sections they are supplemented by draglines for rehandling a small percentage of the yardage, shaping the section, trimming slopes and other miscellaneous duties.



LEVEE ENLARGEMENT (above) with tower-cableway bucket, showing new fill on old levee section, with surface plowed to provide bond.

chines are heavy, costly units, adapted particularly to large-volume, continuing contracts that justify a substantial initial plant investment.

Where the specified limitations of wide, shallow borrow pits make it necessary to skim off earth fill far back from the toe of the levee the tower-cableway machine, with its reach of 700 ft. or more, has proved its effectiveness as a levee builder during the past dozen years. With a couple of exceptions the tower machines are owned and operated by the U. S. Engineer Department, which began purchasing them in 1918. While Government equipment also includes a few large draglines most of the machines of that type are in the hands of the contractors.



HEIGHTENED TOWER MACHINE with steel frame raised about 25 ft., placing top 100 ft. above ground level. Machine stands on banquette of old levee.

All of the Government tower excavators now in service are steam operated, a typical power plant including a 180-hp. boiler, 250-hp. main engine and 50-hp. tracking engine in the headtower, and a 50-hp. boiler and 50-hp. propelling engine in the tail-tower. As the machines are generally operated two 10-hour shifts daily they are equipped with flood lights served by

6 to 10-kw. steam-electric generating units.

Used principally for raising and enlarging existing levees to the new lines and grades of the present superflood levee section the machines operate with the head-tower on the banquette or slightly inclined shoulder of the landside slope of the embankment and the tail-tower just beyond the far limits of the borrow pit. No part of the plant except the bucket, therefore, is in the pit, as is the case with elevating graders, tractor-wagon outfits, draglines and other types of levee-building equipment. This is one of the big advantages of the tower-cableway, especially under conditions of wet, soft

CHarris &

borrow pits encountered so often on Mississippi flood control construction after rains or during high river stages.

Another desirable characteristic of the tower machine is its long reach. The significance of this feature is apparent when it is realized that the enlargement of existing levees necessitates the working of extended borrow pits already partially depleted of



BOTTOMLESS BUCKET is one of many types used on tower-cableway machines.

material and that the Government's specifications place rigid limitations on the depth of cut permissible to secure new earth fill. In the Memphis and Vicksburg districts borrow may not be taken from a point closer than 40 ft. from the levee toe. At the end of this 40-ft. berm the cut starts at a 1 on 2 slope down to a 3-ft. depth and thence extends on an extremely flat slope (1 on 50) to the outer edge of the pit.

Excavation for levee enlargement,



E. S. MAUPIN, engineer in charge of Northern area, Vicksburg district



The

tion

our

wer

to ove ible

wer ers: ing and of out y a nile the the ted

iall

the

ner

way. Size indicated by men cleaning out



ORIGINAL HEIGHT of about 70 ft. is maintained on this tower. (In oval) MAJOR JOHN C. H. LEE, Vicksburg district engineer.



TAIL TOWER of cableway machine operates on bank back of borrow pit.

therefore, especially in borrow pits that have previously been used, is essentially a light, surface-skimming operation, with long haul, rather than a deep cut. Under these conditions it is apparent that in order to secure the required volume of new fill it is necessary to reach far out from the levee toe. With present spans of 700 ft. or more the tower excavator is well



BACK-HAUL CABLE is required on bucket when tower height is insufficient for gravity return to borrow pit.


adapted to this type of work. All of the tower units now in Government service on the river are products of the Bucyrus Company.


Higher Towers — An important change was made last year in some of the tower machines to adapt them to the more exacting requirements of present-day construction. As originally developed for the older and smaller levees, with borrow near at hand, head-towers 70 ft. high were

sufficient to provide a gravity return of the empty bucket along the track cable. With today's wide borrow pits for the enlarged levee sections it becomes necessary either to install a back-haul cable for the bucket or to raise the head towers. Both expedients have been employed. Several machines in the Memphis district have had their head towers raised 25 ft. or so (to heights of about 100 ft.) providing a steep enough slope on the track cable for the return of the empty bucket to the pit by gravity.

Typical Machines—In the accompanying illustrations are shown typical







Page 58

May, 1930—CONSTRUCTION METHODS



DRAGLINES AND TRACTOR WAGON OUTFITS on Arkansas River levee contract of Sternberg Co., Inc.

tower-cableway machines. One, in the lower St. Francis basin near Hayti, Mo., under the direction of G. C. Little, construction supervisor, has a 700-ft. span and a head-tower raised from 70 to 97 ft. It is engaged in adding from 3 to 4 ft. to the height of an existing levee and enlarging the section in corresponding proportion. This machine is equipped with an 8-yd. open-bottom Sauerman bucket. Farther south, near Blytheville, Ark., is a 6-yd. unit with a 650-ft. cableway span and heightened head-tower, under the supervision of J. W. Haskins. Substitution of a 10-yd. Crescent bottomless bucket weighing 9500 lb. on this machine was tried out late last year. under the direction of Major E. C. Kelton, area engineer.

turn

rack

pits

be-

ll a

r to

ents

ines

heir

(to

ng a

able

t to

om-

oical

ACK


HODS

burg district is illustrated one of the 6-vd., 560-ft. span tower machines with 70-ft. head-tower which E. S. Maupin, area engineer at Rosedale, Miss., is using on a "turnover" jobone in which material from an existing levee is excavated, moved inland and reused in the new and higher levee section, set back from the old line. A Bucyrus dragline assists in spreading

In the Arkansas River area is another of the Government's towercableway machines in charge of G. A. Langhofer, general foreman. This machine handles the long-haul earth from the pit and is supplemented by a 125-ft. boom Bucyrus dragline which tops off and finishes the section.

Large Draglines-Dragline excavators on the river work range in size from the light 1 and 1½-yd. crawlermounted machines with 45 to 60-ft. booms for levee slope trimming and wagon loading on haulage jobs up to machines with 150-ft. booms and 5 or 6-vd. buckets. In both small and large sizes the dragline has won wide acceptance as a levee building machine. In all probability a greater yardage of earth fill for Mississippi levees is handled by draglines than by any other single type of equipment.

For draglines in the larger sizes (3 yd. and upward, with booms of 100 ft. or longer) power may be steam, Diesel engine, or Diesel-electric. Gasoline engine power is found generally on machines in the smaller size ranges. The newer large-capacity machines are powered with Diesel-electric plants and there is the possibility of taking electric current from commercial power



CONSTRUCTION METHODS-May, 1930

lines where they may be available near the work. Boom lengths range from about 100 ft. to a maximum of 150 ft. and bucket sizes from 3 to 6 yd.

Where the dragline can work in a borrow pit close enough to the levee to place the earth fill with a single cast it is an ideal machine for flood control work. This condition is encountered more frequently in the New Orleans district than in the Memphis and Vicksburg districts, due mainly to specifications which, for levees below the Red River, reduce the berm width to 20 ft., instead of 40 ft., and permit riverside borrow pit excavation at a slope of 1 on 10 instead of 1 on 50, as called for in the middle and upper delta districts. Under these favorable conditions of deeper borrow fairly close to the levee line much of the work in lower Louisiana is being done with long-boom draglines.

Draglines are prominent, too, in the other river districts, and are sometimes operated in tandem, one machine at the back of the pit feeding another close to the levee. Examples of this scheme of operation are to be found on the Boyce-Igo contract for a section of the Reelfoot levee in Kentucky and on the Arkansas River where the Sternberg Co., Inc., of St. Louis, under the direction of Walker Stansell, is completing some exceptionally high levee (30 ft. or more) with a pair of Monighan walking draglines, one a 72-ft. boom Diesel-operated unit with 2-yd. bucket and the other a Diesel-electric machine with a 125-ft. boom and 6-yd. bucket. For the U. S. Engineer Department W. L. Lipscomb, with headquarters at McGehee, Ark., is area engineer in charge of this work. It is a turnover job involving the placement of 10,000 cu.yd. of fill per 100-ft. station. The photograph on p. 59 gives a good idea of the huge size of this levee and the passing of material from one dragline to another.

The Sternberg organization, at another point on the Arkansas River line, is employing a combination of wagon haulage and dragline work. In addition to 7-yd. tractor-hauled Western and Euclid wagons loaded by a P&H 1½-yd. dragline, a Linn tractor with wheels on the front end and crawlers on the rear end, under a 5-yd. body, is in service on this job.

Dragline Mountings — Mountings for draglines on the Mississippi work

W. A. WELLS (in

circle) area engineer, New Orleans. J. H. LEWIS (left) of Lewis - Chambers

Construction Co., New Orleans. P. H. HEARIN (right) of D. B. Hearin & Son, Baton Rouge.

are of four general types: crawlers (usually on the lighter machines); skids and rollers; wheel trucks and railroad track; and walking tractions. The latter type is confined to the Monighan units and moves the machine 7-ft. at a "stride." Skid and wheel mountings, as illustrated herewith, are common on some of the big Bucyrus draglines in the New Orleans district, notably those of D. B. Hearin & Son, Grasser Construction Co., and Lewis-Chambers Construction Co., all working between New Orleans and Baton Rouge, under the direction of W. A. Wells, area engineer. The Lewis-Chambers machine, on wheel and track mounting is one of the largest-sized draglines on the river having a 150-ft. boom and 6-yd. bucket. It weighs 325 tons.


North of this contract C. I. Jones, contractor, of St. Louis, had just installed a 150-ft. boom Monighan drag-

line with 4-yd bucket.


Much of the levee work north of New Orleans is a set-back operation, involving the use of material from the old levee a few hundred feet from the new line and in some cases an extensive relocation of roads and houses.

The district engineers in charge of the work above described are Lt.-Col. F. B. Wilby at Memphis, Major John C. H. Lee at Vicksburg, and Major W. H. Holcombe at New Orleans, all reporting to Brig.-Gen. Thomas H. Jackson, division engineer, under the general direction of Major-General Lytle Brown, Chief of Engineers.

> NEXT MONTH: Another article on Mississippi River flood control construction.



BIG DRAGLINE, with 150-ft. boom and 6-yd. bucket on Lewis-Chambers contract in New Orleans District.



DRAGLINE with 120-ft. boom and 3-yd. bucket building levee for D. B. Hearin & Son near New Orleans.

### TOB ODDITIES

A Monthly Page of Unusual Features of Construction

SINGLE TRAILER HANDLES BIG LOAD (below). For first time in history of New York subway construction a huge tunnel shield, 20 ft. 5 in. in diameter and weighing 160 tons, was jacked from bottom of 40-ft. shaft, loaded on to an eight-wheel Rogers goose-neck trailer and hauled as a unit, without dismantling, to a new site of operations under Prospect Park, Brooklyn, for the Cornell Contracting Corporation. Cradle of 12-in. timbers, held snug by cables around shield, supports huge load on trailer.

A GUIDE TO GASOLINE. Roadside filling station for motorists at New Bedford, Mass., rich in traditions of the sea, is replica of Government lighthouse nearby. Structure 54 ft. high, 30 ft. in diameter at base displays red beacon on main road between New Bedford, Fall River and Providence, R. I.

ne

a

s, m

se nrs en er e-, of er et.

S,

g-


e e e e

il.

ne al

le


DS



MAMMOTH DIPPER of manganese steel with 15-cu.yd. capacity was cast and assembled by the American Manganese Steel Co. for the Marion power shovel of the United Electric Coal Co. of Danville, Ill. Under the supervision of J. W. Fellmeth, operating engineer, the big excavator is used at the company's Duquoin, Ill., mine for stripping overburden from coal. It is 14 ft. high over the bail, 12 ft. wide between outsides of bail brackets and 14 ft. from ends of dipper teeth to the bottom of the door. It weighs 37 tons.



ALPINE CLIMBING TECHNIQUE is demanded of these workers who clean 500,000 panes of glass in London's Crystal Palace.



STEEL PILING of H-columns carries wharf 1,800 ft. from shore to derrick foundation.

O PROVIDE access to oil-well drilling operations in the Pacific Ocean about 1800 ft. off shore from Seacliff, Calif., near Santa Bar-bara, the General Petroleum Co. last vear awarded to the Robinson-Roberts Co., of Los Angeles, a contract for the construction of a long wharf of special design, comprising bents of H-column steel piling terminating at the seaward end in a submarine foundation of concrete-filled sheet pile cylinders to support the heavy weight of a 120-ft. oil derrick with its rigging and drilling equipment. The recent completion of the structure follows a protracted and bitterly fought legal battle involving rights to drill at sea and access to the work across a strip of beach between the water line and a state highway along the coast.

From the illustration at the top of this page it will be seen that there is an angle in the alignment of the wharf, due to the fact that this location offered the only available access from the state highway to the edge of the lease. Another condition that complicated construction was a state ruling that loaded trucks delivering material to the work could not park on the coast highway longer than 5 min. The wharf itself serves a dual function as a roadway to the oil derrick foundation at sea and also as a connection between the

OIL DERRICK is 120 ft. high, supported by concrete-filled sheet pile cylinders.

first well and others that may be drilled nearer shore at some future date.

The derrick support and dock at the seaside end of the 1800-ft. wharf is a structure 77x200 ft. in plan. Four concrete-filled cylinders of Lackawanna arch web interlocking steel sheet piling, put down through water from 25 to 30 ft. deep, form piers for the legs of the big derrick. The dock is large enough to hold mud tanks, engines, pumps, well drilling supplies and accessory equipment.

H-Column Piles-Departure from previous standards of design is claimed for the Seacliff wharf. With wharves of other types damage is sometimes caused by flotation of the structure when pounding surf puts the sand around the piling into suspension, allowing a heavy ground swell to push upward from underneath the deck and lift the structure. To prevent this contingency and assure ample strength and deep penetration of the supporting piling into the shale bottom which underlies the sandy ocean floor it was decided to use as piles Bethlehem steel H-columns of two sizes, 8-in. on the shore end and 10 in. on the seaward end of the wharf.

Stiffening of the wharf structure is provided by cross-bracing of steel angles, electrically welded to the H-col-

May, 1930-CONSTRUCTION METHODS



TRUCKS deliver material along beach.

ed

he a ur na ig, to of ge

S-

111

ed

es

es

re

nd

ıl-

sh

nd

nnd

il-

T-

ed

01-

re

of

eel

01-

ods




FALSEWORK PILING of wood was used to start the job. Later the driver operated from the permanent steel bents.

umn piles, and longitudinal X bracing

that permits the driving of steel against steel. At the inshore end of the wharf 32-ft. steel piles were used and at the outshore end 50-ft. piles. The piles, after penetrating into the shale bottom of the ocean, were cut off at the proper grade with an oxy-acetylene torch. The pile bents were capped immediately after they had been driven and stringers and decking were placed to form a working platform for the driver as it continued its progress seaward. On the average two bents of four piles each were driven in 8 hours, although

umn piles, and longitudinal X bracing of 1-in. steel rods between alternate pairs of bents which are spaced on 15½-ft. centers, except at the outer end, where a closer spacing obtains. In each bent there are four steel pile columns capped with 12x12-in. timbers bolted down to a steel plate welded to the pile top. Compound stringers of 12x16-in. timber, scarf-spliced over caps where possible, run the entire length of the wharf which is decked with 3x13-in. material. The roadway width is 22 ft.

After falsework piling had first been driven for a short distance from shore to support the pile driving rig steel H-columns, cleaned of mill scale, primed and coated with Biturine enamel, were put down by a McKiernan-Terry hammer having a self-contained anvil block



PILEDRIVER worked seaward from end of wharf as bents were placed.

STEEL H-COLUMNS (in oval) were cut off to proper grade by oxyacetylene torch.

sometimes it was possible to put down three or four bents in the same time.

Derrick Foundation-At the seaside end of the wharf the derrick foundation consists of four 8-ft. diameter sheet-pile cylinders filled with concrete, with a center well cylinder of larger size (14 ft. diameter) for the drill hole. To guide the driving of the Lackawanna arch-web steel sheet piling for these foundation cylinders a steel H-column was first driven at the center of the circle. To it were attached a pair of inner wooden guide rings about 12 ft. apart and an outer guide form held in place by driving from four to six piles. With the guides in place it was possible to drive the ring of interlocking piles to a true circle. After they had reached grade the steel cylinder thus formed was dredged with a small clamshell bucket, a cage of rail

CYLINDERS (right) of interlocking steel sheet piling, were driven, excavated and filled with concrete to form footings for legs of oil derrick and well for drill hole.



ASSEMBLING DER-RICK FRAME (above) of structural steel at end of 1,800-ft. wharf, where space is also provided around the drilling rig for installation of boilers, engines, pumps and other equipment. During drilling all weight is carried by the four leg foundations; when drilling stops weight is transferred to the center caisson cylinder.

DERRICK FOUNDA-TION (below) comprised five cylinders, four 8 ft. in diameter for leg support and one 14 ft. in diameter for well drill hole.



reinforcement was lowered into place and concrete fill deposited, thus forming a footing for the

An important feature of the central cylinder carrying the table from which actual drilling of the oil well is carried on is the installation of a cellar and a conductor pipe extending into the bed of the ocean, sealed to cut off inflows of salt water. In addition a scupper is required to prevent mud and oil from polluting the ocean water.

The time limit for the construction of the Seacliff wharf was 180 days but the Robinson-Roberts organization completed the job with two months to spare. The design of the structure was suggested by C. L. Roberts, member of the contracting firm. Construction was supervised by W. H. Richardson, engineer for the General Petroleum Co. A similar wharf was previously built by the same contractor at Elwood, Calif

Page 64

## Present and accounted For -

A Page of Personalities

9



DERbove) t end where wided ig for s, enother

drillarried undastops ed to inder.

lowconthus or the rrick. entral which arried and a bed flows apper d oil

days ation hs to was er of

n was

built

THODS

W. J. WARD, foreman for the American Bridge Co., in charge of erection of Mid-Hudson bridge at Poughkeepsie, N. Y., described in Construction Methods last month.



JOHN H. BOLTON, of Bolton, Suits, Bolton & Gibbs, highway contractors of Watkins Glen, N. Y., newly elected president of the New York State Highway Chapter of the Associated General Contractors. Mr. Bolton is also town supervisor of Watkins Glen.



NEFF JENKINS, elected to the presidency of the Kentucky Association of Highway Contractors at that organization's recent annual meeting in Louisville.



G. A. BRYANT, JR., vice-president, Austin Co., Cleveland, who heads a group of that organization's engineers bound for Russia to construct a \$50,000,000 automobile factory and industrial city at Nizhni Novogorod.



BOUND FOR RUSSIA. Delegation from Austin Company who have left Cleveland to build huge industrial city and Ford automobile factory near Moscow. (Top row, left to right) T. B. Jorgensen, H. F. Miter, W. J. Austin, G. A. Bryant. Jr., F. J. Moxness, D. H. Kempler, K. Von Havermaet, R. G. Farrington, P. K. Davis and E. T. Smith. (Center row) A. J. Marsh, R. C. Vore, H. C. Patterson. Allan S. Austin, C. F. Appleton, A. F. Surre and W. Baggaley. (Bottom row) Mrs. Havermaet, Mrs. Patterson, Mrs. Allan S. Austin, Mrs. Vore and Mrs. Baggaley.

## NEW EQUIPMENT ON THE JOB

#### New Tongs Make Pipe Line Work Easier

To make flat pipe and pipe line work easier, the J. H. Williams Co. of Buffalo, N. Y., has designed what it calls the Vulcan Boll-Weevil tongs, the operation of which is said to save a great deal of time and effort.

When the tongs are laid on top of the pipe and the chain hooked around it, the proper adjustment for




"making up" or "breaking out" is made without difficulty For "making up" the tongs are slid forward so that the rear end of the jaws engages the pipe and the handle is pushed down. For "breaking out" the tongs are pulled back to engage the forward teeth with the pipe and the handle is pulled up. The arc of the jaws and the shape of the teeth give positive bite. Jaws are reversible for double life. When the teeth first in use wear, the jaws are turned end for end.

The tongs may be had in sizes for \(\frac{3}{4}\)- to 12-in. pipe.

#### Rounds Out Its Line of Hoists

To round out its line of hoists ranging from 4 to 60 hp. in size, the Brown Clutch Co., of Sandusky, Ohio, has developed the Model 30 series in 1-2- and 3-drum types, including boom swinger. These hoists are powered by



24, 28- and 32-hp. Hercules motors. The bronze screw thrust and positive clutch release are standard features of these hoists.

#### Hand Hoist for Truck Bodies

For truck bodies up to 2 tons capacity the Rock Manufacturing Co. of Waterloo, N. Y., has placed on the



market a hand hoist which will dump a load in one minute.

The lifting mechanism consists of upper and lower pairs of lifting arms, the forward ends of which are attached to the body and chassis respectively. These arms are hinged together to form a toggle. Between them, at the front end, is interposed a shaft carrying rollers, which is forced back by the action of the winch to separate them. Practically any tipping angle may be obtained by varying the location of the hoist with respect to the body hinge at the rear.

The hoist is mounted under the body of the truck and requires but 11 in. of space between the body floor and the truck frame. When the body is down, it rests on the side rails of the

truck frame in the usual manner. In this position, the body is locked securely by a strong latch which engages a lug on the winch drum and prevents rattling on the road. It is stated that no drilling is required to attach the hoist to the truck.

#### Improved Rear-Type Crawlers


Improvements and refinements on its model "TG" rear-type crawlers for use on McCormick - Deering 10 - 20



industrial tractors have just been announced by the W. A. Riddell Co. of Bucyrus, Ohio. These new crawlers are particularly valuable for use with power graders and bulldozers where it is necessary that a tractor be maintained on an even keel or where a cutting blade is required to cut to close limits.


#### A Recent Shovel Product

A recent product of the Speeder Machinery Corporation of Cedar Rapids, Iowa, is the Model 90 shovel



of 14-yd. capacity. Like other Speeder shovels the new model has two working speeds on all operations, drums, travel and swing. The high speed is for shovel work; the medium speed for crane or dragline work. Other features are an automatic swing and travel brake, back-geared and purely automatic, which engages as soon as the clutches are released, thus eliminating the burning of reverse clutches, and an automatic power trip for the bucket which can be released by the pressure of a finger tip. The treads are of extra length, 14 ft. 6 in. over all. Gasoline, diesel or electric motors are offered as standard power equipment for this shovel.

## 1 yd. LORAIN 55



A 1 yd. excavating and material handling machine built to the greatest specification a shovel or crane can have—Thew Center Drive.

- A shovel that digs deeper below the treads, dumps higher and farther out than any other shovel of equal length boom and dipper stick.
- A crane that simultaneously hoists, swings, travels with independent control of each operation.





) hp.

vpes,

crew

eder edar novel

eder ork-

ums,

ed is

)ther

and

n as limiches.

the

reads over

otors quip-

HODS

- Mounted on 2 Speed Center Drive Crawler, famous because of low maintenance cost.— Easily extended to longer "64" and "68" tread crawlers with lower ground pressures for crane, clamshell or dragline service.
  - Interchangeable to crane, clamshell, dragline, backdigger, skimmer scoop operation.

THE THEW SHOVEL COMPANY

# HELTZEL Superior Lock ROAD FORMS

Meet New Road Specifications



#### HELTZEL BULK CEMENT BATCHING PLANT

The most economical way of handling cement. Write for full details.

We also manufacture steel forms for streets, curb, sidewalk, curb and gutter, manholes, concrete pipe, steel bins, street joint, measuring hoppers, volume and weighing type, bridges, bulkheads, sub-grade testers, trail graders, mortar boxes, etc. HUSKY road form which permits the use of the most modern road building equipment. A rigid form featuring a positive, tight locking joint and perfect alignment.

Steel stakes, 1 inch in diameter and specially hardened, are held firmly in position by the use of wedges. The stake pockets are so designed that concrete does not clog them.

This form insures a smooth surface, easily negotiates curves and grades. Want further details? Send coupon for literature.

#### The HELTZEL STEEL FORM & IRON CO.,

WARREN, OHIO

Please send me advance information on Heltzel Superior Lock Road Forms. Send your fully descriptive folder to the address given. Name
Company
Address
C.M. 5-30



READY MIXED CONCRETE CORP., RICHMOND, VA., IS CHANGING OVER ALL ITS TRUCKS TO GOODYEARS

#### ISN'T THIS WHAT YOU WANT

#### TO KNOW ABOUT HAULING

#### BUILDING MATERIALS?

You want to know what tires will do the best job for you — what tires will deliver the lowest cost year after year.

ts ad m

ly

he

SO

n.

ly

er

Certainly one of the best ways to find out the best tire for you, is to look at the experience of others.

You'll find that more trucks are equipped with Goodyear Tires more tons are hauled on Goodyear Tires than on any other kind. Isn't that a strong proof that your fleet should be on Goodyears, too?

For hauling building materials, Goodyear builds a special Dump Truck Pneumatic. It's a brute of a tire—extra broad of tread for pulling out of soft ground around excavations—with heavy rubber bars on its sidewalls for extra traction and protection from sidewall gouging. On slower trucks, many use the Goodyear Super Heavy Duty Cushion—and trucks that want to make extra speed on the open road are now adopting the new Goodyear Truck Balloons.

Ask a Goodyear Truck Tire Service Station Dealer to analyze your hauling needs. You can depend on his recommendation for the right tires to use on your fleet.



MORE TONS ARE HAULED ON GOODYEAR TIRES THAN ON ANY OTHER KIND

# HAZARD


### WIRE ROPE

#### SELECTIVITY

There's a Hazard Rope for every class of service FLEX-SET Preformed Wire Rope Armored Wire Rope Improved Flattened Strand Bear Cat Rope —and all standard constructions —the Key to Lower Rope Costs

THERE is a distinct advantage for you in buying wire rope from the company that makes a complete line. This advantage is the ability to obtain properly designed rope for each particular operation.

Take drag line service, for example. You need rope especially designed to withstand severe abrasion—such as Flattened Strand. Or for operations where multiple reeving is encountered, you should use Preformed rope, designed to resist severe bending strains. And for dredging, Armored rope is designed to resist corrosion of the inner wires.



HAZARD WIRE

WILKES-BARRE



ROPE COMPANY

New York

Pittsburgh


Chicago

Denver


Los Angeles

San Francisco


Birmingham



WITH A CONCRETE PLANT



SETTING AND PULLING PILES



A Travelling, Revolving, Long Reach, Heavy Duty Steel Derrick.

# ERSATILITY PUT "WHIRLEYS" ON THE SUISIN BAY BRIDGE JOB

Siems, Helmers and Schaffner, Inc., St. Paul, are putting the bulk of the materials handling on the Suisin Bay job up to three Wiley Whirleys.

Their wide usefulness, adaptation to any mounting and great capacity at long radius, with full circle swing—the same factors that have made them so profitable on other bridge work—made them the choice on this job. One "Whirley" is on a barge with a concrete plant—another on a barge with a pile driver—the third on a barge by itself.

Since 1919 we have been building, exclusively, Wiley Whirleys for clamshell, dragline, crane or derrick work, with 60 to 100 ft. booms. These money making machines have proved all our claims for their strength, simplicity, speed and reliability—for continuous operation with little or no repair expense.

The "Whirley" catalog describes these versatile machines in detail—let us send you a copy.

The DAYTON-WHIRLEY COMPANY

Dayton, Ohio



The Dayton-Whirley Co., Dayton, Ohio

Send the Wiley Whirley Catalog. Where can we see a "Whirley" on the job?

ADDRESS

CONSTRUCTION METHODS-May, 1930

COMPANY ...


DS

Page 71

hatever the job...

AIR-KINGS

do better!



Air power—whether used by the sculptor for carving intricate designs, or used by the workman on a ditch digging job-is certain and dependable when supplied by the powerful "AIR KING".

Actual usage and performance records of AIR KING PORTABLE COMPRESSORS from hundreds of owners are conclusive evidence of their incomparable quality of design and construction—and their faithful dependability under all operating conditions.

M-W AIR KING Portables are second to no compressors in the world. Write for special information. It will pay you to know the facts.

AIR KINGS—embodying such exclusive features as Heavy Duty Industrial Engines with 25% reserve power, "Feather" Valves, Forced Feed Lubrication, All-Welded Steel Frameare made in 28, 110, 220, 280 and 330 cu. ft. sizes—on Towabout, Tractor and Railcar mountings.

Complete Catalog on Request.



METALWELD, INC., 26TH AND HUNTING PARK AVE., PHILADELPHIA Dealers in Principal Cities

#### METALWEL PORTABLE AIR COMPRESSORS



# A NEW service

IN line with the type of service that our many old friends in the road building field have learned to rely on through seventy-two years of satisfactory dealings—we now announce a National Austin-Western Service.


That the users of Austin-Western Road Machinery may never be inconvenienced, an expert service man with no other responsibility and who is a member of the Austin-Western organization, is now stationed at each of the company's branch offices in principal cities throughout the country. Complete stocks of repair parts are also available at all branches. Regardless of where Austin-Western machines are in operation, there is now a responsible repair man with necessary parts within resonable distance.

No longer need contractors or road programs suffer costly and needless delays waiting for some vital part to be repaired or replaced.

This service is just another step in the Austin-Western program for generally improving every road operation and making it cost less—thereby releasing funds for additional operations.

Austin-Western ROAD MACHINERY

# "The BEST rollers that skill and experience could produce!"



# The Fine Austin Autocrat

NO effort has been spared to make the Autocrat the finest roller in the world. Just to list a few of the outstanding features of this peer amongst road rollers is to suggest a quality and performance never before attained in any roller.

Take for example:

The Duplex Worm Gear Drive in the Autocrat gives the greatest efficiency in the transmission of power ever attained in a roller.

The Heavy Three-Speed Transmission permits the use of massive gears with extra large wearing surfaces that will give years of service.

Two Fourteen-Inch Twin-Disc Clutches, forward and reverse, give positive control and ability to reverse direction without changing gears or releasing a master clutch.

A Streamline Frame of Great Strength and Rigidity gives ample support to the massive parts of transmission and motor assemblies.

An Electric Starting System with generator and storage battery.

A Pneumatic Scarifier with Air Compressor Release to throw the compressor out of operation without trouble or loss of time.

Two Reliable Brakes, a foot service brake and a hand emergency brake.

Stored Electricity for parking or headlights.

# And the equally fine Austin Cadet!

The Cadet is the Autocrat of all pupsized rollers. Patterned after the famous Austin Autocrat, the Cadet is a completely factory built, 4-cylinder model, making possible three speeds forward and reverse. It is made in 5, 6 and 7-ton sizes, all of which can be fitted with the patented Austin front planing blade and pneumatic scarifier. A short wheel base—only 8' 1134"—provides ease of operation between forms for concrete roads.

#### THE AUSTIN-WESTERN ROAD MACHINERY CO.

400 North Michigan Avenue . CHICAGO, ILLINOIS . Branches in principal cities

Leaning Wheel Graders, Straight Wheel Graders, Motor Graders, Elevating Graders, Crawler Dump Wagons, Scarifiers, Rock Crushers, Portable Conveyors, Rollers, Motor Sweepers, Street Sweepers, Sprinklers, Road Oilers, Hot Patch Portable Asphalt Plants, Plows and Scrapers.


# STEELTEX lath for plaster GIVES THESE 10 RESULTS —

* MERIT CHART	Ribbed STEELTEX for Plaster
Reinforcing	1
Insulation	1
Sound deadening	. 1
Automatic back-plastering	1
Adds structural value	1
Added security over suction or plaster keys	1
Angle reinforcement at no added cost	. 1
Assurance of having proper and uniform thickness of plaster	1
Prevents lath marks from showing on finished plaster	1
Crack prevention	1

Ribbed STEELTEX, the modern plaster lath and steel reinforcement, protects the beauty, value and permanence of plaster walls and ceilings . . . and safeguards your investment.

Use Ribbed STEELTEX lath for plaster walls and ceilings and you will get all ten results as shown in the merit chart (at left).

Any plaster lath will give some of these results, but to obtain a first-class plastering job, all ten results, as indicated in the chart, are of vital importance. Ribbed STEELTEX lath gives all ten results. Previously limited to costlier dwellings only, Ribbed STEELTEX is now suitable, practical and economical for every type of home or building . . . large or small.



Ribbed STEELTEX for interior plaster is the easiest handled lath on the market and comes in bundles ready for application. Ribbed STEELTEX lath is quickly and easily applied and when plastered becomes a one-piece, solid reinforced plaster slab...like reinforced concrete in principle.

The reinforcement of Ribbed STEELTEX is composed of a network of cold-drawn, electrically-welded steel wire (heavily galvanized). This steel network is securely woven onto a tough, purefibrous backing. Across the back of the STEELTEX sheet are rows of v-shaped metal rib stiffeners . . . insuring board-like rigidity. Ribbed STEELTEX provides all the modern requirements of a highly satisfactory plaster lath and steel reinforcement. There are other interesting details about Ribbed STEELTEX . . . sign the coupon below and get the facts.





Ribbed STEELTEX lath is easily handled.



Application of Ribbed STEELTEX is rapid




Reinforcement minimizes plaster cracking hazards

### NATIONAL STEEL FABRIC COMPANY

Pittsburgh Steel Co

UNION TRUST BLDG. PITTSBURGH, U.S.A.

Gentlemen:—Please send (free) descriptive STEELTEX literature,
for interior plaster  for stuceo  for brick and stone veneer  for floors  for roofs  for
Firm Name
Individual's Name
Address



## \*A3BEAM,3 COMPARTMENT BUTLER WEIGHING HOPPER

A NEW 3-beam scale that meets the most rigid requirements of the toughest job where speed and easy, dependable operation are important.

This new Weighing Hopper is designed to meet the new specifications of the Joint Committee of the American Association of State Highway officials and the Good Roads Association. This makes it eligible for all state and county work.

It is a marvel of compact, simplified equipment that is easily operated under all conditions. Be sure to get full information on this new Butler product before deciding on new weighing equipment.

BUTLER BIN COMPANY, Waukesha, Wisconsin



BUTLER Steel BINS



\*This scale can be furnished

in the 2-beam type where

conditions do not require

the use of the 3-beam type.









# NORTHERN KINGS POWERED >> AND PORTABLE





Northern Kings offer greater capacity, more economical upkeep and unceasing operation; they are the finest conveyors built!

HENEVER a belt conveyor may be used, Northern offers a model that will operate with greatest efficiency.

In all the field there is none to compare with the Northern King series . . . for they are built to specifications which assure the use of finest materials to complete a belt conveyor beyond anything offered by any manufacturer, anywhere!

... and, because every step of manufacture is controlled within the great plants of Northern... because everything used (excepting only wheels, cables and drives) is fabricated by Northern, it follows that the user benefits to this extent: He gets, in a Northern Conveyor, MORE for equal money... more in capacity, more in the materials which make the conveyor a lasting investment!

Northern King Conveyors are the world's standard . . . nationally sold and serviced.

Write!



HODS

NORTHERN CONVEYOR & MANUFACTURING CO.

Dept. 20, Janesville, Wisconsin

FACTORY BRANCH: 13712 TYLER ST., DETROIT, MICH.

BRANCHES AND STOCK POINTS.

SAN FRANCISCO, CALIF. NEW HAVEN, CONN.

ST. PAUL, MINN.


ROCHESTER, N. Y. PITTSBURGH, PA.

# INANCING Single Units or Complete Plants

BUYERS OF POWER often foresee large savings through the installation and operation of their own power plants. Producers of Power often foresee similar savings through modernization. By using the Commercial Credit Plan both buyers and producers are effecting these sayings without the aid of increased capital, bond issues or the impairment of operating funds.

Commercial Credit Plans are designed to allow payment for machinery and equipment of all kinds, from earnings. These plans have proved sound in practice. If yours is a replacement or expansion need there is a Commercial Credit Plan ready to serve you.

Write, today, for full information.





#### COMMERCIAL EQUIPMENT CORPORATION

Commercial Equipment Corporation, affiliation of Commercial Credit Companies, provides a further financing service to industry. Its method of financing complete installations as a unit, requiring two or more varying types and makes of equipment, has been approved and endorsed by many of the country's leading engineers.

COMMERCIAL BANKERS CASH CAPITAL and SURPLUS \$58,000,000

COMMERCIAL CREDIT COMPANY COMMERCIAL CREDIT CORPORATION - New York COMMERCIAL CREDIT TRUST . . . . Chicago COMMERCIAL ACCEPTANCE CO. . Indianapolis

MIDWEST COMMERCIAL CREDIT COMPANY, Detroit, Des Moines, Mile

COMMERCIAL CREDIT COMPANY, Inc., New Orleans COMMERCIAL CREDIT COMPANY . San Francisco New York KEMSLEY, MILLBOURN & CO., Ltd. AMERICAN CREDIT CORPORATION - Omaha

CONTINENTAL GUARANTY CORP. of CANADA, Ltd., Montreel

NATIONAL HEADQUARTERS, Baltimore

COMMERCIAL CREDIT COMPANIES, Baltimore, Mary	rland
	without obligation, about Commercial Credit Plans.
Firm Name	Ву
Address	Title



# FOR YEARS

Map shows location of Concrete Steel Company's Warehouses

Camden, N.J., Warehouse, Concrete Steel Co.

FOR a quarter of a century, the Concrete Steel Company has served the construction industry. Today it maintains well-stocked, perfectly-equipped warehouses at strategic points throughout the country. At these depots all reinforcing material is cut, bent and fabricated to specification. It then is delivered to the job on a pre-determined schedule day by day to suit your requirements.

Such is the SERVICE that Concrete Steel Company is in a position to render you in supplying reinforcing material. Let us figure on the specifications for your next job.



Executive Offices: 2 Park Ave., N. Y.

DISTRICT OFFICES— Birmingham, Boston, Chicago, Detroit, Milwaukee, Minneapolis, Philadelphia, Pittsburgh, St. Paul, Syracuse, Washington.

Concrete Steel Co.

# FIVE GREAT TRACTORS





# that span the full range of your working needs!

HERE is power—cheap, dependable, profitable—to match your small jobs or your very biggest. Whether it's building new highways or maintaining old ones—excavating for a reservoir, filling in a lake front or laying out a suburb—the Cletrac line provides a choice of power units to economically meet all operating needs.

Back of these modern Cletracs is fifteen years of exclusive manufacture of "crawler type" tractors. Built into them are the many advancements and refinements that only specialized manufacture can develop.

Investigate these tractors — their records for speed, capacity, endurance — their unmatched economy of operation. Let us place the full story before you — or arrange with your local Cletrac distributor for demonstration.

## THE CLEVELAND TRACTOR COMPANY

19323 Euclid Avenue, Cleveland, Ohio

Cletrac Crawler Tractors



# This Industrial Acceptance Indicates Preference

Listed here are a few outstanding Mahon Steel Roof Deck installations.


9

American Brass Co. American Coil Spring Co. American Gear Mfg. Co. Apollo Steel Co. Armstrong Cork Co. Arvey Corporation Bohn Aluminum and Brass Briggs Manufacturing Co. Brunswick, Balke, Collender Co. Buick Motor Car Co. Cadillac Motor Car Co. Campbell. Wyant & Cannon Co. Columbus Union Oil Cloth Co. Continental Steel Co. Detroit Edison Co. **Durant Motor Car Co.** Eastman Kodak Co. **Fisher Body Corporation** Fostoria Glass Co. Frigidaire Gemmer Mfg. Co. General Railway Signal Co. Glasscock Mfg. Co. Hupp Motor Car Corp. Ingersoll Rand Co. Larkey Foundry Co. Latrobe Electric Steel Co. Liquid Carbonic Co. Nichols Copper Co. Oakbrook Hosiery Mills Inc. Oakland Motor Car Co. Olds Motor Car Co. Packard Motor Co. Pennsylvania Light & Power Co. Pennsylvania Railroad Robert Buyer Corporation Rossman Corporation Timken Roller Bearing Co. U. S. Navy Warner Aircraft Corporation Wilcox Rich Company L. A. Young Industries

Below is a cross section of Mahon Steel Roof Deck showing application of insulation and roofing material.



Mahon Steel Roof Deck, manufactured from special tight coated galvanized copper bearing steel, requires no painting or maintenance whatsoever . . . it provides a smooth rigid surface for the application of insulation and roofing material.




Mahon Steel Roof Deck installed on a new plant for the Latrobe Electric Steel Company, Latrobe, Pa.

THE broad acceptance of Mahon Steel Roof Deck among the outstanding industrials of the country is significant of two things: First, that Mahon Steel Roof Deck is thoroughly practical in every respect . . . and that the ease of installation, and the principle of load distribution through lateral continuity, has gained for it a decided preference among architects and builders; Second, that architects, builders and manufacturers are availing themselves of the economies and the firesafety and permanence provided by this modern type of roof. Mahon Steel Roof Deck is less than half the weight of the lightest roof in other types of permanent, firesafe construction. It is rolled from special tight coated galvanized copper bearing steel...it will not disintegrate, and it requires no painting or maintenance whatsoever. In buildings designed to carry this extremely light roof load, savings amounting to as much as 25% can be effected in the supporting steel alone. Let us show you the economies and the structural advantages of Mahon Steel Roof Deck. Write for our complete data book and our folder, "Facts and Figures."

#### THE R. C. MAHON COMPANY DETROIT, MICHIGAN

Representatives in Principal Cities





When you lose valuable time because of breakdowns, adverse weather conditions, or other emergencies—

Put Carbic Flood Lights to work!

Bring your work up to schedule—and keep it there. Any time is working time for the contractor equipped with Carbic Flood Lights.

Carbic Flood Lights afford ideal illumination for night work. Their powerful rays enable your men to work rapidly and safely at night. There is no glare, and no dark shadow. Penetrates fog, smoke or dust to a remarkable degree.

The initial cost of the Carbic Flood Lights is low, and the operating expense is negligible.



Carbic is distributed by

the Union Carbide Sales Company through its na-

tional chain of warehouses and is sold by

PROCESSED CARBINE FOR CARNIC LIGHTS & GENERATORS

#### **OXWELD ACETYLENE COMPANY**

Unit of Union Carbide and Carbon Corporation NEW YORK

Sales offices in principal cities


Technical Publicity Dept., CM-5-30 12th floor 205 East 42nd Street, New York, N. Y.

Without obligation, I would like to have additional informa-

City......State.....

USED ON THE PIERS OF NEW HUD-SON RIVER BRIDGE AT 176TH ST., NEW YORK CITY.







### Wherever Nuts Are Turned Time and Money Can Be Saved

By Using THE

#### FAVORITE Reversible WRENCH

It works with the quick, straight ahead ratchet movement, and wrench head does not leave the nut until operation is completed.

Compare this with the time wasted by the old fashioned open end wrench that has to be removed from the nut at every part turn for a fresh hold—unnecessary lost motion.

Has the socket form of head that encompasses the nut on all sides with equal pressure. This tends to prevent wrench from slipping off nut.

Leading Contractors use the "FAVORITE" Wrench for speeding up the nutturning portion of the contract, especially where the saving of time is a very important consideration.

Write us for full particulars.


Greene, Tweed & Co.

Sole Manufacturers

109 Duane St., New York



# a little Master



#### Galion Distributors

Galion Distributors

W. A. Adams Tractor & Equip. Co., Raleigh, N. C.
R. S. Armstrong & Bro. Co., Atlanta, Ga.
O. B. Avery Co., St. Louis, Mo.
Badger Tractor & Equip. Co., Milwaukee, Wis.
W. D. Banker Road Machy. Co., Memphis, Tenn.
Banks-Miller Supply Co., Huntington, W. Va.
Borchert-Ingersoll, Inc., St. Paul, Minn.
Brown-Fraser & Co., Ltd., Vancouver, B. C.
Dukehart Machy Co., Des Moines, Iowa
Easton Tractor Co., Cambridge, Mass.
Feenaughty Machy. Co., Portland, Ore.
Frankfort Equip. Co., Frankfort, Ky.
Good Roads Machy Co., Inc., New York, N. Y.
Hall Perry Machy. Co., Butte, Mont.
Herd Equip. Co., Oklahoma City, Okla.
Interstate Machy. & Supply Co., Omaha, Nebr.
Jeffrey Mig. Co. Ltd., Montreal, Que.
Jenison Machy. Co., San Francisco, Cal.
C. H. Jones Co., Salt Lake City, Utah.
Lewis-Patten Co., San Antonio, Texas.
Lewis Tractor & Machinery Co., Fargo, N. D.
Marsh Equip. Co., Colby, Kan.
Miller & Requarth, Springfield, Ill.
Morrow Auto Co., Albuquerque, New Mexico
H. W. Moore Equip. Co., Denver, Colo.
Morrisey Easton Tractor Co., Vicksburg, Miss.
Murphy & Murphy, Little Rock, Ark.
C. T. Patterson Co. Inc., New Orleans, La.
G. C. Phillips Tractor Co. Inc., Birmingham, Ala.
Power Equip. & Service Co., New Haven, Conn.
F. Ronstadt Co., Tueson, Ariz.
Smith-Booth-Usher Co., Los Angeles, Cal.
Standard Road Equip. Co., Rockford, Ill.
W. H. Stoutenburg, Penn Yan, N. Y.
Tennessee Tractor Co., Nashville, Tenn,
F. E. Vaughn, LaCrosse, Kan.
Virginia Road Machy. Co., Richmond, Va.
Welch Good Roads Supply Co., Welch, W. Va.

For those who have known and used the Galion Master, the Galion Little Master Roller needs no introduction other than

to say . . . that it is like its larger brother in design and

The Little Master embodies, to a degree never before attained in a small roller, the same simple unity, rigidity, strength and handsome appearance found in the Master Roller.

The Little Master uses the same transmission and Twin Disc Clutch that have proved so successful in the famous Galion Master. One piece heavy steel side frame plates . . powerful steel pinion and gear . . and renewable phosphor-bronze bearings for the rear axle are only a few of the features that make this Roller truly the Little Master of big jobs.

A Hercules Model K, 4-cylinder, 4-cycle motor furnishes the power for the Little Master. Three sizes . . 6, 7 and 8 tons.

There's a Galion Roller for every job. Write the Galion distributor nearest you for bulletins describing them.



The Galion Iron Works & Mfg. Co.

construction.

PUT 17

A simple material-moving idea that is earning thousands of dollars for contractors all over the country


Each Barber-Greene Conveyor Belt is a broad, swiftly moving highway that carries what you have to move in a steady, non-stop stream—from where you have it to where you want it.

Carries up to 300 lineal feet, and elevation angles up to 35 degrees are not uncommon.

You simply put the stuff on one end and watch it come off the other.

The flexibility of Barber-Greene Setups, which can include one or more portable or permanent conveyors, is almost unbelievable.

For these standardized units can be arranged and re-arranged to meet almost any condition, cheaply and efficiently.





Wet concrete direct to forms



Sand and gravel at the central plant



Mixer to forms on small job

BARBER



**GR** 

WATCH

Where you see wheelbarrows, concrete carts or expensive material-moving machinery, Barber-Greene Conveyors can likely supply you a new and surprising answer—at surprisingly low costs.

The holds for sand, gravel, wet concrete, brick, refuse, bagged or bulk cement, or what have you.

We can't begin to list the many common and unusual applications on which Barber-Greene Conveyors are earning money for contractors. Each day, it seems, a contractor works out a new cost-cutting use.

But we will be glad to send you our latest conveyor application book which details a variety of different conveying jobs—New Applications and Set-ups—if you will

but fill in the coupon tear at the dotted line and send to: Barber-Greene Company, 530 West Park Avenue, Aurora, Illinois.





Filling two batcher bins




Sand, gravel, excavated material



Pouring floors in a big building

EENE

BARBE	R-GREENE Send me					Illinois
Name		 	 		 	
Address		 	 		 	
City			 State	e	 	



On the Job
with the
DRAVO
CONTRACTING
COMPANY

PITTSBURGH

BUILDING BRIDGES

Sixteen of these husky Lowell Wrenches were furnished for this one bridge job. And that was after the Dravo Company made exhaustive tests on the safety, dependability and economy of Lowells.

The tests proved that when a Lowell is fixed to a nut, the man is safe in putting all of his energy into driving the nut tight. For Lowells don't know how to fail—they don't slip—they're built with a wrench knowledge of 60 years. And the ratchet feature is a distinct economy. There is no lost time in re-fitting the wrench to nut—once there, the Lowell stays put 'til the nut is pumped tight.

Lowells can play an important part in saving time on almost any construction job. Write for Catalogue "R," which shows you how.

#### LOWELL WRENCH COMPANY

WORCESTER, MASSACHUSETTS

You'll Like This Oil Burning Kettle

> Style "J" Made in 50-, 75-, 100- and 165-gallon sizes



Here are some of the reasons why every highway department should use Connery's Style "J" Oil Burning Kettle:

Two-compartment hinged covers. Barrel grids underneath.

Easy working pressure pump

Fuel tank copper brazed, galvanized inside and out. Stays in same position when trail-ing and in operation. Cast steel pulling ring.

Valve control of temperature. Improved Connery Oil Burner.

Heavy duty axle.

Heavy duty standard roller bearings with large grease cups in wheel hubs.

Connery's Improved Springs absorb road shocks.

Rubber-tired wheels (optional equipment), Steel wheels with roller bearings standard.

Heat-resisting guards to protect rubber tires from heat (optional equipment). Connery's patented tubes and stiffeners, prevents outside shell from warping.

Inside tank removable for cleaning. Materials No. 10 and 12 steel, inside tank and outside shell; except 165-gallon kettle, which is made of No. 10 entirely.

Oil Burner can be removed for thawing in winter, or other purposes. Heavy improved drop leg.

Heat-resisting steel guard to protect fuel tank from heat. Non-leakable draw-off faucet.

Removable wind-shield to protect burner.

Equipped with Hand Spraying Attachment, Style "J" Oil Burning Kettle will guard any highway with economy and efficiency. Easy to handle—quick to heat. A first-rate investment that always pleases.

We manufacture a full line of Tar and Asphalt Kettles, Oil Burning Kettles, Pouring Pots, Torches, Hand Spraying Attachments, etc. Send TODAY for our illustrated "Blue Book."

CONNERY & COMPANY, INCORPORATED American & Luzerne Sts., Philadelphia, Pa.





#### THE "HY-LO"

Think about public safety and protection of your interests in the light of Dietz Red Lanterns - best understood and most dependable signal lights used on road construction jobs at night — unequalled for low cost and oil saving.

Dietz "Hy-Lo" Hot Blast Lantern has a popular feature in its direct globe lift. The globe is lifted upward by one finger-no lever being required.

#### R. E. DIETZ COMPANY **NEW YORK**

Largest Makers of Lanterns in the World



# reverore

### have you seen Buckets like these!

For ability to dig hard material, the new WILLIAMS "Champion" goes beyond any previous bucket.

In all our experience we have never seen the equal of the new WILLIAMS "Champion" for digging power— and for speed.

21 improvements—including the narrower and more rigid head—the larger diameter sheaves—sturdier corner bars, extending beyond the scoops and giving extra leverage—all-welded scoops of new easy-filling design—and many other improvements, have made it possible to place the new WILLIAMS "Champion" on your work with the definite guarantee to Outdig and Outspeed any other bucket built.

Before you buy a bucket, it will pay you to try the new WILLIAMS "Champion"—it challenges competition, and invites comparative test.

#### G. H. WILLIAMS COMPANY

607 Haybarger Lane, Erie, Pa.

Branch Offices: New York, Pittsburgh, Chicago







Although cables were strung from cranes as a precaution in moving down grade, they proved entirely unnecessary. as the extra large Rogers brakes on all 8 rear wheels provided ample braking power.

106 Orchard Street

Albion, Penn.

#### CALDWELL BROTHERS & BOND BROTHERS

GENERAL CONTRACTORS
SIS EGWARD AVENUE
TRANSCORD EATTORS \*\*\*\*
NEW ORLEANS

March 31st, 1930.

Lone Star Cement Company 1120 Hibernia Bank Building, NewOrleans, Louisiana.

Gentlemen:

Answering your inquiry as to our use of your "INCOR" cement in the construction of the Municipal Auditorium:

We take pleasure in giving you the following data:

Our contract with the City of New Orleans for the Municipal Auditorium = \$1,565,000.00 - was signed on February 15, 1982, and work started two weeks later. As you probably are aways, it was specified that the Auditorium should be turned over to the City on January 1, 1930, with a penalty of \$500.00 daily for each day's delay thereafter.

We have no hesitancy in telling you that our completion of this job on schedule time was largely due to the use of "INCOR", your High Early Strength Portland Cement.

The original specifications stipulated forms were to remain in place twenty one days after pouring of concrete. You can appreciate what it meant to us to be able to remove the basement column forms, and to back fill within twelve hours after pouring with "INCOR".

By using "INCOR", we obviated the necessity of using any admixtures, and all of our waterproofing was done with this cement.

We are writing you this as an indication of our entire approval of "INCOR" cement, which we used with every degree of success, and expect to take advantage of its high early strength qualities on many jobs in the future.

Actual facts

Very truly yours,
CALDWELL BROTHERS & BOWN BROTHERS
For

New Municipal Auditorium, New Orleans, Architects: Favrot and Livaudais. Contractors: Caldwell Bros. & Bond Bros.

READ, in the above letter, how "INCOR"
Brand Perfected High-Early-Strength Port-

land Cement helped make it possible to open the magnificent New Orleans Municipal Auditorium on time.

"INCOR" ends costly delays—makes possible completion of more and larger contracts during one construction season—lowers overhead costs—releases equipment sooner.


"INCOR" contains no admixtures... requires no special methods of handling. It combines the outstanding quality of Lone Star Cement with the added advantage that "INCOR" produces *Portland Cement* concrete that is ready to use in 24 hours.

SUBSIDIARIES OF THE INTERNATIONAL CEMENT CORPORATION 342 MADISON AVENUE, NEW YORK, N. Y.

LONE STAR CEMENT CO. INDIANA, Inc.
THE CUBAN PORTLAND CEMENT CORP.
LONE STAR CEMENT CO. PENNSYLVANIA
THE LONE STAR CEMENT CO. (KANSAS)
LONE STAR CEMENT CO. VIRGINIA, Inc.
LONE STAR CEMENT CO. NEW YORK, Inc.
LONE STAR CEMENT CO. LOUISIANA
ARGENTINE PORTLAND CEMENT CO.
LONE STAR CEMENT COMPANY TEXAS
URUGUAY PORTLAND CEMENT COMPANY

#### INTERNATIONAL CEMENT CORPORATION

LONE STAR



Large-diameter power shafts of heat-treated chrome alloy steel. Double-come hoisting, crowding and sluing frictions. Base, furntable and boom heavily constructed and completely electric welded. In fact, every part designed to withstand the hard knocks to which small excavators are subjected.

Speed and ease of handling also are features of the Model 4. Accelerator controlled 40-hp. gasoline engine equipped with variable-speed transmission. Travels % to 3 miles an hour, and will climb a 25 per cent grade. Fast crowding, hoisting and swinging enables this new machine to make five trips per minute in regular operation.

The Model 4 is readily convertible to shovel, crane, dragline, ditcher or skimmer. Write for details and prices.

ORTON CRANE & SHOVEL CO.

608 S. Dearborn Street, Chicago, Illinois Representatives in Principal Cities

ORSTONIES SHOWERS SHOWERS



IE

ON

MA

IIA

# Concreting a canal with "CATERPILLAR" TRACTORS

WATER flowing through this canal is used five times for power—once for irrigation. So it's precious—it is worth while to line the canal and reduce friction and seepage. Four "Caterpillar" Thirtys are on the job; each machine helps concrete 300 linear feet a shift, hauling material and moving the outfits ahead. And the "Caterpillar" can

turn around in these cramped quarters.

Power, traction and dependability!

Prices—f. o. b. Peoria, Illinois
TEN . . \$1100 TWENTY . \$1900
FIFTEEN . \$1450 THIRTY . \$2375

#### Caterpillar Tractor Co.

PEORIA, ILL. and SAN LEANDRO, CALIF., U. S. A.

Track-type Tractors Combines Road Machinery
(There's a "Caterpillar" Dealer Near You)



\*The Bear River Canal Enlargement Project of the Pacific Gas & Electric Co., Colfax, California

IRACIOR



# TRACTOR SHOVELS SMONTHS

WHAT better recommendation for any piece of equipment? When the Carlton Company started work on a section of the Brooklyn subway construction they called on their two BAY-CITY Tractor Shovels to clean up the loose earth, rocks and boulders left by the big shovels. So well did these speedy, mobile, efficient machines do their work (equipped with special booms to reach in under the low roof at the sides and in between supports) that the Carlton Company ordered a third Bay-City in December and a fourth machine in January.

And now—they have wired for two more Tractor Shovels, equipped with short 18 ft.

crane booms and convertible for shovel service.

These machines are operating two shifts—day and night—with a saving of many hand laborers and much time. All of which brings us up to the fact that the Tractor Shovel is not intended for work which requires the power and strength of a ¾ yard machine. It is rather designed to fill the gap between hand labor and heavy high-priced equipment—to handle those jobs which do not require large, heavy machines and which can be handled more economically with smaller equipment.

Repeat orders of this kind emphasize BAY-CITY popularity and superiority. Write for Catalog T-6 and further information.

BAY CITY SHOVELS, Inc. BAY CITY, MICH.

New York Office-302 Broadway

BAY-CITY SHOVELS

THE BAY-CITY FAMILY

WORLD NEWS STORIES OF THE KOHLER ELECTRIC PLANT-No. 18



#### guiding the ships of air and sea

THROUGH the night sweeps a powerful beam over land and sea, signalling safety to navigators of air and water. Confident eyes watch for these lights from the cockpits of mail planes; officers on the bridges of liners, freighters and private craft check and set their courses. Power from Kohler Electric Plants operates hundreds of these beacons and these lighthouses.

Over 1000 Kohler Electric Plants are in use by various departments of the U. S. Government. Of the latest shipment of 110, one hundred are being installed along the airways for visual and radio beacons and ten in lighthouses, giving reliable, automatic, independent electric power that safeguards life and property. Other governmental users include the Army and Navy, the Department of Justice (standard and emergency lighting for prisons and prison camps), National Park Service, Indian Irrigation Service, Commission of Forestry and the Coast Guard. Scores of these plants are used on cruisers and destroyers.

Kohler Electric Plants generate current at 110 volts D. C., or 3-phase 220 volts A. C. Capacities from 800 watts to 10 K. W. They make night work practical, safe and profitable. For floodlights, operating motors, pumps, air compressors, lathes, portable electric tools. Kohler Plants are compact, rugged, self-contained and can be transported over rough country without damage. They operate without storage batteries. For complete information, send the coupon today. Kohler Company. Founded 1873. Kohler, Wis.—Shipping Point, Sheboygan, Wis.—Branches in principal cities. . . . Manufacturers of Kohler Plumbing Fixtures.

# KOHLER OF KOHLER ELECTRIC PLANTS KOHLER CO., Kohler, Wisconsin Gentlemen: CM 5-30

Please send catalog describing Kohler Electric Plants.

Name\_\_\_\_\_Street\_\_\_\_\_

City\_\_\_\_State\_\_\_

Use in which interested.



### 150,000 Toledo Torches

Everywhere, under a wide variety of difficult conditions, TOLEDO Torches are doing a real job of safety lighting. Driving rain, hail, snow or stiff, tricky winds never dim the bright, warning flare of these sturdy, indestructible little sentinels.

The demand for these torches is steadily increasing because TOLEDO Torches are better. Better because they are different. Different because every TOLEDO Torch is equipped with our patented Economy burner, which cuts fuel cost in two — eliminates wick consumption.


Insist on the genuine TOLEDO Torch. Your dealer can supply you



Manufacturers of the Toledo Folding Steel
Horse—the ideal highway barricade




# "We Procure Maximum Quality and Minimum Prices



Above—Mr. G. A. Voorhies and Mr. W. F. Burr, of The Youngstown Rubber Froducts Company of Youngstown, Ohio. This company's services are of a definite economic value to the prosperity of its business territory.

ANUFACTURERS approach us knowing they are in competition with others who desire the volume we have. They realize that to earn our volume they must offer a maximum of quality at minimum prices. This price advantage we bring to consumers. Our recommendations are worthy of thought, and we recommend Republic's Belting—Hose—Packing—Molded and Lathe Cut Goods."

The above statement is characteristic of those made by prominent distributors all over the country. It explains in part how the Industrial Supply Distributor, helping to solve the important problem of broad markets and economical distribution, upholds high quality, maintains fair prices and saves needless efforts on the part of both consumer and manufacturer.



Whether it be for sand suckers—loading or unloading oil, or, molasses, or, such work as contractors must do every day, Republic's Suction Hose will meet every requirement economically.

Send For Sample.

## THE REPUBLIC RUBBER CO.

Youngstown Ohio



### DIFFICULT? Yes, but a WARCO Does It!



WARCO One-Man "Road-Hog" power graders are engineered—not just assembled.

They are expected to do construction work, in keeping with their size (and you have three sizes for selection), as well as high class, fast maintenance.


WARCO oscillating rear-type crawlers hitch the power of your tractor to the ground. WARCO head-type steering, and three point motor suspension make such jobs as this possible.

Three sizes—six models—center and rear control power graders.


You owe it to yourself to thoroughly investigate WARCO graders, wheeled scoops and rear-type crawlers before you buy.

W. A. RIDDELL COMPANY, BUCYRUS, OHIO.

Power and Drawn Graders — Wheeled Scoops — Rear-Type Crawlers for Tractors



# Cutting Material Handling Costs with Hercules-Powered Tractors




general contracting—compact, powerful Tructractors save time and money in material handling.

Hercules Engines are the choice of leading manufacturers of industrial machinery. They meet a wide variety of heavy-duty requirements—for they are available in Four and Six cylinder models ranging from 13 to 115 H.P. Manufacturers and users alike know that Hercules power is a virtual guarantee of reliable, low-cost operation.

HERCULES MOTORS CORPORATION, CANTON, OHIO West Coast Branch: Los Angeles, Cal. - Mid-Continent Branch: Tulsa, Okla.

## HERCULES ENGINES





## That FIENDISH DECIMAL POINT

How many times has it got YOU in bad? Like the contractor who, in a competitive bid on some construction work for the State of California, priced an item as .21—when it should have been \$21.001 Fortunately the State did not stand on its legal rights and the contractor escaped a big loss.

Such mistakes CAN'T happen when you put your figuring up to the Marchant Portable Calculator. Its "mechanical brain" does all the exacting, tiring, time-consuming work for you. And it's absolutely accurate—right the first time and all the time.

Wherever your work is—out on the job, in camp, in the office—the Marchant will figure for you far faster and better than you can do it yourself.

ANYONE CAN RUN IT with ten minutes practice. A compact, light-weight, high-grade machine that will give years of satisfactory service.

Sold under the Marchant guarantee of satisfaction. Terms if desired.

Don't waste any more time and effort on pencilpushing figuring. Mail the coupon now.

MARCHANT PORTABLE Calculator \$



Adds Subtracts Multiplies Divides

17 years building calculators, nothing else. Electric, hand operated, and portable models as low as \$125.

Free! Marchant Calculating Machine Co.
Dept. 141, Oakland, California

Please send me full information about

☐ Marchant All-Electric ☐\$125 Marchant Portable

Name	
Firm	
Address	
City and State	

#### THE RIGHT TOOL SAVES TIME

#### EXTRA HEAVY

This road rake is forged from one piece of bar steel. It is extra heavy, being designed to fill the needs of road builders and paving contractors. Will stand up under hardest kind of service.

An excellent tool for spreading heavy materials such as gravel, crushed stone, and concrete.

This rake has 14 teeth. Head is 3% inches deep, and 15% inches wide. Handle is 5½ feet long.

The brand True Temper is burned in the handle to mark each rake as the best tool of its kind that can be made.

THE AMERICAN FORK & HOE CO.

1901 Keith Bldg., CLEVELAND, OHIO

Makers of Farm and Garden Tools for over 100 Years

Branded on the handle of every genuine TRUE

TEMPER

If your dealer has not yet stocked the True Temper Steel Road Rake, Cat. No. X14, send us his name and \$1.70 and we will supply you direct, postpaid.

STEEL ROAD RAKE





F R E E

Heavy Steel Goods or Industrial Tool Catalog. Describes over 50 tools for mill, mine, factory and coal yard.

TRUE TEMPER

## CHECK, these FEATURES

Lower Overhead Room—
Total height is but 8'-07/8"
to top of the batch hopper.

2 Drum Rollers—genuine car wheel metal with chilled face and flange. Timken Roller Bearings.

3. Drum—all steel construction large radius corners. Mixing blades equipped with highcarbon steel renewable liners.

And that is speed! Power discharge is standard.

5. Accurate and Rapid Water

Control—One turn of the control wheel changes from the maximum to the minimum that can be discharged from the tank. This change can be made instantly and no locking device is needed on the wheel.

It is impossible to by-pass any water through the poppet valves used only on the Ransome 28-S.

6. Lubrication—Alemite through-

Before You 28%

You'll Find Them All

Insome.

in the NEW


Bulletin 124 tells the whole story. Send for your copy today or ask any Ransome distributor for one.

Ransome Concrete Machinery Company
1850 - Service for 80 Years - 1930

Dunellen

New Jersey

#### Heavy Traffic Means Rush Work



CLEVELAND ROCK DRILLS Street cars transport thousands of people across this bridge every day. Traffic is heavy. Delays must be avoided, yet repairs must be made. That means night work—rush!

Cleveland C7 Paving Breakers with their unusual speed, power and punch are ideal for fast demolition work. That's why this street railway company\* owns 45 of them.

Let us tell you more about the Cleveland C7. Write.

\*Name upon request.

#### THE CLEVELAND Rock Drill Company

3734 E. 78th St., Cleveland, Ohio Distributors in 111 Cities of the U. S. have parts in stock.

HOISTS BUILT ESPECIALLY FOR CONTRACTORS

DAKE DAKE DAKE DAKE DAKE

Longer Life...Greater Strength... Less Weight...and far in advance of the ordinary, are

#### DAKE S-LG HOISTS!

The Chrysler Building, the tallest in the world would have been impossible without the use of structural steel. Think of it—over 1,000 feet high, 76 floors housing over 11,000 people.

DAKE uses structural steel in the S-LG HOISTS. This permits greater strength per pound of weight—easier movability—long life.

DAKE HOISTS as modern as skyscrapers. They are constructed to meet every requirement of the contractor.

Regardless of your lifting problem, there is a DAKE HOIST that will efficiently solve it.

Write for our interesting catalog. Investigate our special dealer proposition.




DAKE ENGINE

Grand Haven Michigan DAKE DAKE DAKE

DA DA DA D





THESE double butterfly train sheds—recently erected for the Terminal Railroad Association of St. Louis—were originally designed for riveting.

The Mississippi Valley Structural Steel Company, upon receiving the contract, redesigned the structural steel for arc welding—thereby effecting a substantial reduction in price and assuring pleasing, symmetrical structures whose joints were less liable to attack by the corrosive smoke found in steam terminals.

The outstanding success of these arc-welded sheds will appeal to all progressive railroads and will greatly simplify the problems of the construction engineer. Complete details of this job and of G-E arc-welding equipment are available to all interested. Simply address General Electric Company, Room 311, Building 6, Schenectady, N. Y.

JOIN US IN THE GENERAL ELECTRIC HOUR, BROADCAST EVERY SATURDAY EVENING, ON A NATION-WIDE N.B.C. NETWORK

GENERAL & ELECTRIC

## TRUSCON STEEL DOORS



### **Built To Withstand** Hard Usage

Truscon Steel Doors are built to last-built to withstand the hardest punishment to which doors can be subjected. These high quality, sturdily built doors provide the best of protection for industrial buildings, garages, hangars, service entrances, etc. Furnished either in standard stock types or in special designs to meet individual needs. Truscon engineers will cooperate gladly in developing the right door for every type of building. Write for Door catalog.


#### TRUSCON STEEL COMPANY

YOUNGSTOWN, OHIO

Steel Door Division

Truscon Steel Company of Canada, Limited Walkerville, Ontario

Warehouses and Offices in Principal Cities




Standard Single Swing Type Steel Doors.



Standard Double Slide Type Steel Door.



Costs Are Low



## 2500 feet of air needed to meet varying demand!


This foundry has just installed its fifth Balanced Angle Compressor

TWELVE years ago, a large foundry in Boston installed its first Balanced Angle Air Compressor, selected for its manifest advantages in power and upkeep economy.

Four years later, Balanced Angle No. 2 was added, based on the performance of No. 1.

In 1923 and 1926 additional, larger Balanced Angles were installed. In 1930 one of the small machines was replaced by another large Sullivan. Today the capacity of the air power plant is approximately 2500 feet, and consists of four units.

These compressors are individually driven by electric motors with short-center belt connection. One, two, three or all four may be operated at a time, according to the demand for air.



Angle Compounds are favorites, not only in foundries, but in manufacturing, utility, railroad and Engineering installations the country over. Their exact balance, compactness, low overall cost and high efficiencies are unique.


Have you investigated Sullivan compressors? Capacities 68 to 5100 cu. ft. All drives. Catalogs on request.

### SULLIVAN AIR EQUIPMENT

SULLIVAN MACHINERY COMPANY

816 WRIGLEY BLDG., CHICAGO

30 CHURCH ST., NEW YORK







Portable Sawing Machine



At the New Ford Plant Edgewater, N. J.

(a

Hundreds of oak piles to 28-in. diameter to be cut. At one time, a long, costly, hand job. Now, the Timber Wolf makes short work of such timber cutting—two men cut 5 times as many timbers as before.

The contractors on this job are Allen N. Spooner & Sons. They, like hundreds of other construction men, have learned the speed and the low ultimate cost with which the Timber Wolf cuts piling and timber.

Write for list of users.


With A.C. or D.C. Drive or Compressed Air Drive for under-water use.

REED-PRENTICE CORPORATION

WORCESTER, MASS., U. S. A.

# They're smooth,

# those streets and highways in the State of Iowa!



the photograph. And it will stay smooth, almost indefinitely, because it is protected with Carey Elastite Expansion Joint, installed at frequent cross-intervals.

One of the principal highways through O'Brien County, Iowa, surface-smoothed for years and years to come with Carey Elastite Expansion Joint.

ONTRACTORS and road-builders in lowa make a thorough job of it. They keep those highways through the prairies smooth (and the city streets, as well). They protect the concrete against expansion and contraction; and, at the same time, they safeguard their own professional reputations. With the origi-

nal, pioneer Carey Elastite Expansion Joint!

The famous Carey Elastite Expansion Joint is made in

"sandwich" form-asphaltic and fibre compounds, between sheets of asphalt-saturated felt. On highspeed highways and boulevards, in city streets, in bridges and dams and culverts, it protects concrete for years and years against expansion and contraction strains. An indispensable improvement-yet it adds

but the smallest decimal to the total construction cost.

Write for the free "Elastite" manual on expansion joint installation.



THE PHILIP CAREY COMPANY Lockland, CINCINNATI, OHIO

# **Priming** HUMDINGER **Centrifugal Pumps**

HUMDINGER FEATURES

TWENTY-SEVEN FOOT SUCTION LIFTS GUARANTEED—NO FOOT

Continuous Automatic Prime-takes water as it comes to hose.

Large Air Capacity—Quick Priming-Exceptional on well point systems.

Open, Three Vane Non-Clogging Impeller-Will pass lots of mud and sand.



Write for literature

WORTH KNOWING ABOUT

NO PRIMING PUMPS OR COM-PLICATED MECHANISMS — NOTHING TO GET OUT OF ORDER.

Rugged Construction — Ball-bearing Pumps — Chrome Alloy Impeller — Stainless Steel Shafts.

Capacities from 100 to 1,500 gallons per minute.

Prices that will give you a pleasant

HACKENSACK, N. J.

#### RALPH B. CARTER COMPANY



a gang. Spots railroad cars, draws concrete forms, shifts tracks, handy on steel erection, warping barges, wrecking, tightens guy wires-

warping barges, wrecking, tightens guy wires-lifts, shifts, pulls, holds. 1,000 uses on every job. Good for 10,000 lbs. pull.

At your jobbers or order direct. Outfit includes 3½-ft. tail chain, 15-ft. load chain and sheave block—for changing direction or double-strength pull. Complete \$36.00 f. o. b. works, Reynoldsville, Pa. (Longer chains quoted). Write for bulletin No. 25.

T. H. EFELBLUTE COMPANY Oliver Building \$ Pittsburgh, Pa.

Also Manufacturers of "Anchor" Track Braces and "Anchor" Rerailers





DOBBIE SHEAVES

For Concrete Towers. Elevators, Head Shafts, etc., with Cast Steel or Semi Steel Sheaves

For Heavy Loads High Speed and Long Lifts use Ball or Roller Bearing Pillow Blocks instead of Plain Bearings



DOBBIE FOUNDRY & MACHINE Co. Niagara Falls, N. Y.

Complete Stock Carried at Niagara Falls and New York City

Timber Derrick Fittings-Sheaves-Hand-Winches-Blocks Write for prices, Dobbie all steel Derricks and Rotating Derricks.

# Omaha Airport . . . solves its drainage problem this way . .





(Meet copper-bearing pure iron requirements in all accepted specifications for corrugated metal culverts.)

© 1930 G. C. M., Inc.

# Have Stood the Test of Time

Have Stood the Test of Time
GOHI Corrugated Culverts
that have been in service for
twenty years have been found,
upon examination, to be practically perfect and good for
undetermined years of additional service.

# Corrugated Culverts

THE progressive city of Omaha is draining its modern sixty-acre airport with GOHI Corrugated Culverts. It has selected this modern culvert for its proved permanence—its rapid, low-cost installation—its strength which withstands the impact of heaviest planes—its flexibility which prevents breakage under the terrific pressure of freez-

ing water or settling earth fills.

Made of Genuine Open Hearth Iron — pure Iron-Copper alloy — these culverts offer maximum resistance to corrosion and give lowest-cost-per-year service of any culvert material. Get ALL the facts and you'll specify GOHI Corrugated Culverts.

#### GOHI CULVERT MANUFACTURERS, Inc., Newport, Ky.

Central Culvert Co.
Ottumwa, Iowa

Denver Steel & Iron Works Co.
Denver, Colo.

A. N. Eaton, Metal Products

Feenaughty Machinery Co.
Portland, Oregon

Lincoln Steel and Forge Co.

The Newport Culvert Co.

The Pennsylvania Culvert Co.
Philadelphia, Pa.

Roanoke Sales Corp.

St. Paul Corrugating Co. St. Paul, Minn.

Tennison Brothers
Oklahoma City, Okla.

Tennison Brothers
Texarkana, Ark.

Capital City Culvert Co.

# New and Enlarged



# Now! Six Volumes

—for every contractor, engineer, and architect who is looking for practical information on every day construction problems—

The Dingman books have long held an enviable position among the builders and building contractors. Their reputation has been established on their sound and practical treatment of construction work.

Now, newly enlarged to six volumes, and actually reduced in price, the Dingman Library offers a most complete source of ready reference. It is invaluable, too, as a course of study for searchers after a broader knowledge of building.

# The New Dingman Building Contractors' Pocket Library

6 volumes, 1149 pages, pocket size, fully illustrated

will help the building contractor to increased profits through the use of modern business practice—will help the construction engineer and foreman to speedier methods and greater efficiency—and aid the student to a mastery of the many details of modern construction.

Practical data is given on analyzing a construction job into its component parts—estimating the costs of labor, haulage, equipment, materials, etc.—plan reading and determining quantities from specifications—personnel management—successful supervision of every building operation—efficient and economical business methods—office procedure such as accounting, banking, purchasing etc.—advertising and selling methods for contracting service—and a complete data book of tables, forms, and calculations most frequently used by the builder.

Fill out and mail the coupon for a 10 days' FREE EXAMINATION of this new six-volume Library.

# MCGRAW-HILL FREE EXAMINATION COUPON

McGraw-Hill Book Co., Inc., 370 Seventh Avenue, New York, N. Y. You may send me for 10 days' free examination, the new six-volume Dingman BUILDING CONTRACTORS' POCKETBOOK LIBRARY. I agree either to return the booke at the end of 10 days or send a first payment of \$1.50 then and \$2.00 a month for five months.

Signed

Address

City and State

Official Position

# Add a WAPPAT Electric Handsaw To Your Payroll

and you will find that it will take the place of ten men with old handsaws. By using this modern labor-saving tool you can cut operat-

ing costs and make greater profits. Have your nearest dealer demonstrate on the job. May we send our catalog?



We also manufacture drills, grinders and mortisers.

WAPPAT

44 Braddock Ave., Pittsburgh, Penna.

Division of Simond's Saw and Steel Co.



How well those responsible for the design and fabrication of

#### Buffalo-Springfield ROLLERS

have wrought is evidenced by the fact that there are more Buffalo-Springfields on the roads and streets of America, both on maintenance and new construction, than all other builders of such equipment can account for.

Built in all practical sizes, threewheel and tandem, steam and motor driven. Scarifler and other attachments optional. Write for illustrated booklet.

The Buffalo-Springfield Roller Company



# EFFICIENT HEAD WORK


The headwork of man conceived and made economically possible the building of the giant skyscrapers of today and the headwork of engines has made possible the use of equipment that has brought these giant buildings into being.

Just as the capacities of men vary according to their mental ability, so do engines vary according to the ability of the head to control economically the energy generated in the combustion chamber.

Therefore, the most outstanding development in gasoline engine design in recent years is the patented Ricardo Head, an important feature on all Fuller & Johnson vertical engines.

The Ricardo Head achieves greater agitation of the gases in the combustion chamber at the moment of ignition; the flame is fanned through the entire mixture with lightning rapidity, effecting more nearly

complete combustion with as much as 20 per cent fuel saving; "after-burning" is eliminated and exhaust



Model AH, 6 hp. single-cylinder engine with roller bearings and Ricardo Head.

temperatures reduced several hundred degrees, making for cooler

valves, more power and longer life.

It is efficient headwork to specify "Fuller & Johnson", the engine that good equipment deserves.

For further information concerning the engine illustrated or other Fuller & Johnson power units write the Fuller & Johnson Mfg. Co., manufacturers of single and multi-cylin-

der... air and water cooled... horizontal and vertical engines, in various sizes. Address: Fuller & Johnson Mfg. Co., 50 Coma Street, Madison, Wisconsin.




# FULLER & JOHNSON

ENGINE SPECIALISTS

ESTABLISHED 1840

Powerful Enough for The Big Job!



CALL on a Schramm to do any kind of job. It will come through and ask for more.

Ochramm I

Representatives in All Important Cities

West Chester Penna., U. S. A.

New
Answers
to
Pumping
Problems



The REX PUMP BOOK tells a new story of value and efficiency for all contracting pumping jobs—from well-point systems to supplying a 27-E Paver—from pile-jetting to emptying a trench or manhole. If you're looking for new, efficient pumping—if you want the most pump

your money can buy—



Get a copy of the REX PUMP BOOK today with this coupon.

CHAIN	BEI	LT	COMP	ANY
764 Park	St.	M	ilwaukee,	Wis.
Name			*******	

Address.....Clty....

State....

# DIXONS



# DIRTPROOF AND STEAM PROOF TOO..FOR JOBS LIKE THIS

Are you protecting the life of your costly equipment by keeping dirt, water, steam, etc., out of the bearings. You will be glad to know that you can—with Dixon's Waterproof Graphite Grease. This lubricant has flake graphite as the vital, wear-resisting element combined with high-grade lubricating stock—double insurance of better lubrication.


Use Dixon's Waterproof Graphite Grease on chains, wire ropes gears, heavy bearings, etc., especially where exposed to the weather or difficult operating conditions. Get acquainted with this unusual lubricant and you will find out the wisdom of using it regularly. Write for Circular No. 86-W.

Joseph Dixon Crucible Co.

Jersey City



New Jersey



# · · costs down

There is a threefold way to prove that Dodge Trucks lower hauling costs and increase profits for contractors. Simply ask owners, inspect and compare these workers and test one—with you behind the wheel.

By such thorough investigation you will know that Dodge Trucks have the power to pull, the speed to save time, the dependability to maintain schedules, the economy to save money, the long life to lower depreciation costs, the good looks to attract patronage—all qualities that keep costs down and profits up.

There are 124 standard Dodge Trucks to select from. They are built in capacities ranging from ½-ton to 3-ton, in various wheelbases, with optional gear ratios, tire sizes and body types. Your Dodge Brothers dealer can show you the one that fits your needs.

# DODGE TRUCKS



Showing Curcrete being applied on Division Road, Royal Oak, Michigan Sed in 28 States!

The Curcrete process for curing concrete has proved to be so thoroughly satisfactory that the use of it increased a hundredfold in one year, so that in 1929 Curcrete was used in curing more than 10 million square yards of concrete pavement.

What is Curcrete? A special emulsion of bitumin—applied in the form of a fine spray to freshly finished concrete, before it has obtained its initial set. Its use stops the evaporation of water from the concrete immediately, thus preventing surface checking and subsequent scaling, and at the same time assuring maximum and uniform strength.

With all its advantages, the Curcrete method costs no more than any other method of curing. One gallon of Curcrete covers 8 to 10 square yards, and 150 to 200 square yards per hour can be cured by our specially-designed pressure sprayer and bridge, operated by one man. Also, no cleaning up is required.

Write today for interesting booklet telling all about the Curcrete method and giving results of tests.

#### THE BARBER ASPHALT COMPANY

New York Chicago PHILADELPHIA
Pittaburgh St. Louis Kansas City
San Francisco

San Francisco

"Curcrete" (trade-mark registered) is sold for use in the curing of concrete by the "Curcrete" method (U. S. patents 1,539.763 and 1,684,671, and foreign patents pending) controlled by The Barber Asphalt Company. The Barber Asphalt Company grants to the purchasers of "Curcrete" the right and license to practice the "Curcrete" method of curing concrete, controlled by it, in connection with the use of "Curcrete" produced by it, and the purchasers by accepting "Curcrete" accept the license and acknowledge the company's rights in connection with the "Curcrete" method.



## The BEST at any Price!



This Transit is designed to meet the most exacting requirements of the Construction Engineer, and is Kolesch Quality throughout.



#### KOLESCH & COMPANY

138 Fulton St., New York, N. Y. Established 1885

## BULL FROG WHEELBARROWS

#### They Hold Down Costs

Dependability of equipment is a vital factor on the modern construction job where delays may mean the difference between a profit and a loss. That's why more and more contractors are standardizing on Bull Frog wheelbarrows, carts and scrapers. They have proved their stamina and easy-handling qualities on all types of jobs. There's a model for every contracting and industrial need. Ask your supply house, or write for catalog showing the complete line.


## THE TOLEDO WHEELBARROW CO. TOLEDO, OHIO

Branch Office and Warehouse: CHICAGO-520 W. Erie St.

The Buil Frog Concrete Cart is the sturdlest cart you can buy. Made in two sizes, the larger of which can be supplied with either plain or roller bearings.



# Have you a Good Hoist for that



The Hoist With The EXCLUSIVE BRONZE SCREW

No wobbly side frames, consequently no breakage—Let us tell you why!

The New Model 30 Series is available in single, double and triple drum units as well as Boom Swinger.

Bouipped with new Series 24, 28, 32 or 35 H.P. Hercules Power Unit; rating 3,000 to 4,000 pounds single line pull at 200 feet per minute; Morse Silent Chain final drive; 10 in. diadrums; large bronze bushings; Four bolt bearings; Flanged gear guards; Exclusive Bronze Screw Thrust; positive clutch release; Timken and Ball Thrust Bearings; Alemite lubrication throughout; side frames cast separate from base; shrouded pawl ratchet cast separate from drum; spring suspended easily adjusted brakes; non-spreading side frames; machine cut nickel semisteel gears, etc., etc.

Old equipment, like old methods, are too costly for today's needs.

\*One of the largest construction companies in the country recently purchased three new big double drum BROWN "GIANT-LINE" HOISTS (one with boom swinger) although they have a yard full of old hoists of almost every make.

You, too, will save money by junking old equipment—using new, modern, dependable BROWN "GIANT-LINE" HOISTS.

There is a size and type adapted to every requirement from 4 to 50 horsepower—each representing an outstanding value.

New 1930 Catalog B-1 upon request.

## The Brown Clutch Co.

Sandusky, Ohio, U.S.A.

BROWN

\*Name upon request.

SINGLE & MULTIPLE DRUM - REVERSIBLE

NON-REVERSIBLE AND CONVEYOR TYPES

CHOISTS

HOIST SPECIALISTS FOR A QUARTER CENTURY

CONSTRUCTION METHODS-May, 1930

Page 115





Model DR, 11/2 cu.yd.

Model KR 1 cu-yd.

#### **Baker Maney Scrapers Now With Roller Bearings**

You may now have Baker Maney Self Loading Scrapers in 1 cubic yard and 11/2 cubic yard capacities equipped with Timken Tapered Roller Bearings—a feature which insures greater operating efficiency and longer life.

The same short-turning ability—great strength and quick loading and dumping features which have built for them their reputation as efficient dirt movers are retained. Plain bearing models in  $\frac{3}{4}$ , 1, and  $\frac{1}{2}$  cubic yard capacities are still available.

Send for 32-page catalogue on Baker Maney Scrapers—"the original self loaders."

THE BAKER MANUFACTURING CO., 568 Stanford Ave., Springfield, Illinois



Write For These Bulletins:

Baker Maney Scrapers

**Baker Rotary Scrapers** 


**Baker Bulldozers** 

**Baker Maintainers** 



#### Now Ready!

The latest information for reference and study in your field -the valuable experience of men who are widely recognized as experts-is contained in McGraw-Hill books. You have the key to this experience in the



#### New 1930 McGraw-Hill Catalogue of Engineering and Business Books


THIS catalogue describes more than 1500 books covering all branches of engineering, science and business. Our latest publications and the newest revisions of standard works are listed.

This catalogue outlines a plan whereby you can put your book-buying on a convenient budget basis. Get the books as you need them-pay for them by the month as you use them.

We have reserved a FREE copy for you-Send for it-TODAY!

\* McGraw-Hill Book Company, Inc., 370 Seventh Avenue, New York. Send me the new 1930 McGRAW-HILL CATALOGUE of Engineering and Business Books, to the address given below. This catalogue is to be sent entirely without cost,

Name .	 	 	 
Address	 	 	 



## Standard of the World

Gasoline-Electric-Steam Derricks

Car Pullers—Cableways

J. S. Mundy Hoisting Engine Co. 722 Frelinghuysen Ave., Newark, N. J.

> TRADE MARK \* ESTABLISHED 1869

Export Office, 30 Church Street, New York City Cable Address: BROSITES

CON



## "Here, Lad-

I'm with you in putting this fellow 'Acr Welding' to work for us, but we've got to know more about him before we go ahead."

# The Lincoln "Stable-Arc" Welder

- welds easier
- makes better welds
- permits greater output because of the steady uniform arc throughout entire welding range, which is the result of:

Variable voltage design Laminated magnetic

circuit

Separately-excited generator field

Double control of welding

heat
All steel construction

No other welder has all these features.

#### "No, Pop-

You mean before we go behind.

The way I look at it, the taking on of an arc welding machine isn't one whit different from taking on an employee.

First he's got to prove to us that he has specialized experience and thinks straight.

It's a matter of record that the thinking behind the Lincoln 'Stable-Arc' welder has been straight since it pioneered the art.

When those people took up specialization in arc welding equipment they advocated variable voltage.

Those not in welder specialization said 'No'.

How many say 'No' today?

How many say 'Yes' today?

And again comparing welders to employees—do you prefer 'Yes Men'— or specialists in the Know?"

The Lincoln Electric Co., Dept. No. 32-5, Cleveland, O.

CAre" WEIDER

# Lectro molded BOOT

For excavating work....a new boot molded in one piece like an automobile tire Greater Ease and Longer Wear



The Lectro Molded Boot is built by an entirely new and different method to best withstand the grinding, cutting wear of sand, rough gravel, rocks, concrete, mud, water—every kind of hard going in construction work.


This new boot is actually molded in one piece under enormous pressure that makes the rubber many times tougher than ordinary boot stock. If your supply house cannot supply you with Lectro Molded Boots, write for a pamphlet which describes fully the unique features of this new boot.




The Lectro Molded Boot is patented and made only by

HOOD RUBBER COMPANY, INC. Watertown, Mass.

HOOD MAKES CANVAS SHOES . RUBBER FOOTWEAR . TIRES
RUBBER SOLES AND HEELS . RUBBER FLOOR TILING







# BROWNING 5/8 YARD SHOVEL

A NEW and finer gasoline shovel . . . a fast, powerful digger . . . built to "stand the gaff" . . . goes anywhere under its own power . . . steers easily from the cab . . . quickly convertible to crane, trench hoe, or dragline.

For complete details, specifications and prices write any office listed below.



16226 WATERLOO ROAD . CLEVELAND, OHIO, U. S. A.
BRANCH OFFICES: . NEW YORK, N. Y. . CHICAGO, ILL.
DISTRIBUTORS

Birmingham Montreal San Francisco Los Angeles Syracuse Tacoma Minneapolis Toledo, O. Baltimore Tulsa, Okla. Portland Toronto New Orleans Albany Kansas City Indianapolis Charlotte, N. C. St. Louis Victoria, B. C., Canada







## Easy on the Hands-Gluttons for work

Sabin Co., Gloves.
536-46 W. Federal St., Youngstown, Ohio.
Send me information on Sabin Gloves.

Name

Address

If you wish a pair of No. 206 Gloves, Enclose \$1.50 and check here 

...

You've never put your hands in more comfortable gloves—nor owned a pair that stands up like Sabins.

Their palms of grey buffed cowhide with outseam mean comfort for the palms. The holdtight back keeps them from falling off.

Price \$1.50 per pair. Send cash, check or money order for a pair and get acquainted with Sabin's gloves.

Sabin Co.—Gloves

536-40 W. Federal St., Youngstown, Ohio





When you go after a steel pipe project, take Biggs along. You then have on your side an ally with years of knowledge and experience in all that pertains to the subject of steel pipe, both welded and riveted.

and Do the Job

Biggs stands ready to furnish you the technical data and information which will help you secure the job. Having secured it, you can further turn over to Biggs the complete responsibility for laying the pipe and for handling such details as are involved. You may depend upon Biggs service to account for all the little things essential to completing the installation quickly, economically and satisfactorily.

When the next pipe project comes up, give the Biggs organization an opportunity to work with you.



Inspectors for New York, Detroit, and Boston, approving sections of Biggs welded steel pipe after test. Diameters, 36 in. to 72 in. The contracts involved approximately 50,000 feet of electrically welded pipe for installation on major projects in those cities.



Riggs 30 in. diameter Electric Welded Steel Pipe installed for Department of Water Supply, Gas and Electricity, New York City, Job 7900 ft.



Biggs \2 in. diameter Electricially Welded Pipe being installed for the City of Detroit, Dearborn project.

#### **BIGGS BUILDS**—

Welded Steel Pipe Tunnel Shields
Riveted Steel Pipe Air Locks
Pontoons Welded Tanks
Caissons Riveted Tanks
Steel Plate Construction of Every Description

#### Biggs Welded Steel Pipe

Biggs Welded Steel Pipe, with its smooth interior and maximum structural strength, insures safe, economical, permanent conduit. It withstands more distortion and stress than any other type. It affords maximum carrying capacity. It guarantees uninterrupted service and minimum maintenance, especially under severe conditions. The Biggs weld is stronger than the plate itself.

Biggs' facilities and service are presented photographically in "Unusual Steel Plate Construction." This folder is yours for the asking. Mail us the coupon below.

THE BIGGS BOILER WORKS COMPANY Kent Street and Case Avenue, AKRON, OHIO

New York

Detroit

Chicago

BIGGS Steel Pipe
Riveted and Welded



The Biggs Kent Stree									Р,		A	k	r	Di	n,	,	0	h	ı	0.			
Send us '	Unusual	-		te	e	1	1	?1	a	te		(	10	H	19	t	ri	16	et	Î	98	n°	
UNUSUAL STEEL	PLATE			ø	ø					v	ø								*				,
CONSTRUCTIO		*		×							*		×				*		- 16	*			×
			*							*		*	*	*	*	×			*	×			
MAN POLEN VONES O	- CANADANY							*				٠		*	*	é	,					2	

#### TEMPLE & CRANE, MC.

CONSTRUCTION

COURSE & CRANE

CHAMBER OF COMMERCE BUILDING

March 17, 1930.

Mr. T. F. Moore, President, Moore Trench Machine Company, Rockaway, N. J.

Dear Mr. Moore:

Our recent contact with your Company was so particularly satisfactory that it deserves a letter of appreciation from us.

The new Power House at Bristol, Conn., for the New Departure Manufacturing Company offered a water problem which was most successfully met by the use of your Wellpoint System. The site was covered with ground water when we took possession and previous studies had indicated the presence of ennumerable springs in the area which we had to excewate for a minimum depth of about 22'. The meterial was of fine sand which became decidedly "quick" as the excavation went down.

The use of Steel Sheet Piling and Pumping might have been successful but without doubt considerable time and expense was saved by the use of your wellpoints.

We followed the recommendations of your engineers as to the details of installation and found no occasion to change them in any way as the work developed.

The system not only removed all water but gave us a compact bottom on which the steam showel could operate successfully in the deepest excavation. It minimized the sheeting requirements and proved of considerable advantage in the shoring of the bank which supported adjacent Railroad tracks.

The results certainly met all expectations, and confirmed our opinion gained from previous experiences.

Yours very truly,

Temple & Crane, Inc.

Bdw. H. Temple & Temple &

ERT.JR/E

## AS ALWAYS

Satisfactory contact.

Site covered by water.

Springs and quicksand.

Sheeting saved. Time and expense saved.

All water removed. Compact bottom for shovel. Railroad tracks supported. Met all expectations.


## "MORETRENCH"


That's all.

Thank you, Mr. Temple.

MOORE TRENCH MACHINE COMPANY, Rockaway, N. J.











Western Drag Scraper made in 3 sizes.



Western Fresno Scraper Made in five sizes



Western Wheeled Scraper Made in five sizes



Western Tumblebug Scraper Capacity, 1 cubic yard

# Use Western Tools for your Short Haul Work

Western short haul tools have been the contractors' standard for many years, some being originally designed over 50 years ago. It is not on past performance that Western equipment has gained its reputation. It is today's performance and the continuous improvement that has kept them abreast of the times that is responsible for their high standing.

The scrapers shown on this page are designed for specific purposes. They have ample strength to do the work they may be called upon to accomplish and will do it quickly and easily.

Catalog 29ED thoroughly explains the working range and the many unique features of the entire line of Western small tools. Where shall we mail your copy?

Western Wheeled Scraper Company Aurora, Illinois, U. S. A.

WESSERN

# Hotstuf

#### Can You Use an Extra \$6.00 plus Profit per Day?

That's the added profit that HOTSTUF owners make daily on a crew of 5 men.

Based upon a crew of 5 men at \$4.00 per day per man and using 150 working days per season there is a time labor saving amounting to \$900.00 per year over any other heater on the market. Plus a fuel saving of 30% or 48 cents per day. A fuel saving for the season of \$72.00.

Model "T"

The Patented Elevated Melting Chamber accounts for this greater efficiency and extra savings.

Multiply \$972.00 by the number of HOTSTUF Heaters to be used and you have added many extra thousands of dollars profit to your work.

The MOHAWK HI-SPEED TRAILER is an all steel box especially designed to meet the requirements of the progressive contractor. Compartments, fittings, partitions are all worked out from the practical suggestions of the men on the "firing line". Made of heavy steel. All seams are electrically welded. Double covers are waterproof and can be locked down. Made in 6, 7, and 8 foot lengths.




Write today for Catalog No. 12. It tells the HOTSTUF story.

## MOHAWK ASPHALT HEATER CO.

62 Weaver St., Schenectady, N. Y.

# MORRIS CENTRIFUGAL PUMPS



MORRIS PUMPS are made in all desirable types and sizes, motor, steam or gasoline engine, belt or chain drive, for domestic water supply, boiler feeding, circulating, irrigating, drainage, sewage disposal, hydraulic dredging, sand production and conveying, handling clean, dirty or acid water, etc.

Many popular types and sizes constantly in stock, and special designs built for unusual head, speed or capacity conditions. The advice of our Engineers on any pumping problems is free for the asking. Write for literature.

#### MORRIS MACHINE WORKS, Baldwinsville, N. Y.

Originators of Centrifugal Pumps, both Single and Multi-Stape, and builders for practically all purposes since 1864.

Brench Offices:—New York, 225 W. 34th St.; Philadelphia, Witherspoon Bullding: Cleveland, 1367 E. Sixth St., Chicago, 228 N. LaSalle Street; Boston, 79 Milk Street; Pittsburgh, 328 Second Avenue; Detroit, Fisher Bullding; Charlotte, Realty Bidg.

Sales Representatives: - Buffalo, Kansas City, Omaha, Huntington, W. Va., Houston, and in other industrial centers.

Canada: Storey Pump & Equipment Co., Toronto.



# A Sensational Performer and Money Saver


THE speed, versatility, rugged construction, big yardage and low cost of the Fundom combination shovel, ditcher and crane, make it a sensational performer and money saver.

It makes small jobs profitable. Fast, full  $\frac{3}{4}$  circle swing,  $\frac{1}{3}$  yard dipper capacity,  $\frac{16}{2}$  foot radius, gasoline power.

With Trench Hoe attachment for ditching or Boom Extension for clamshell, dragline or crane, the Fundom is an unbeatable three-in-one digging machine.

Get the details and name of nearest dealer. Address-

The Fundom Hoist & Shovel Co. 314 Central Building, Lima, Ohio



# **CONTINENTAL SUCTION HOSE**

"Not the Cheapest but the Best"



Smooth Bore

These Constructions are the Secret of long life and flexibility



Rough Bore

#### Write Our Nearest Branch for Prices and Information:

ATLANTA, GA419 Ponce de Leon Ave.	DAYTON, O122 So. St. Clair St.
BALTIMORE, MD112 W. Pratt St.	DETROIT, MICH5423 12th St.
BOSTON, MASS200 Congress St.	NEW YORK, N. Y152 Chambers St.
BUFFALO, N. Y	PHILADELPHIA, PA313-319 New St.
CHICAGO, ILL	PITTSBURGH, PA300 Penn Ave.
CLEVELAND, O203 Perry Payne Bldg.	ST. LOUIS, MO221-223 No. 3rd St.
TOLEDO, OHIO	415 Michigan St.

Continental Rubber Works, Erie, Pa.

C. C. Kerner, 152 Chambers St., New York, N. Y., Exclusive Foreign Representative

# PERFECTION BODIE

The Greatest Money-Maker in Years

THE PERFECTION ALL-STEEL DROP SIDE DUMP BODY

With its many new and modern improvements virtually eliminates competition.

A Dump Body of ample capacity that may be quickly converted from a tightly closed body to a wide, open platform. Sides may be quickly removed, if desired. Sturdy, collapsible stakes fold in when body is closed and do not interfere with loading. Equipped with Hand, Gravity, Combination and Mechanical Hoists. Patents pending. Here's something you can't afford to overlook.

THE PERFECTION STEEL BODY CO.

Dept. C.M. Galion, Ohio, U. S. A.



	dy Co., Galion, Ohio, Dept. C.M. information on the New Perfection Drop
Name	*************************
City	***************************************
State	***************************************





#### You Can Prevent Concrete Failures

Frequent compression tests are not only now required on all large contracts, but are absolutely essential from a standpoint of safety.

The illustration shows one of our 200-ton hydraulic presses arranged especially to test concrete test cubes, cement, stone, etc.

We also build Jacks for underpinning and heavy lifting; Bending Presses for bending pipe, bars, etc. Shears for reinforcing bars; Punches for structural shapes, etc.


Write for Bulletins

#### THE WATSON-STILLMAN CO.

1014 Evening Post Bldg., New York City
Chicago, 228 N. La Salle St.
Cleveland, Penton Bldg.
Pittsburgh. Union Trust Bldg.
Houston, Union Nat'l Bank Bldg.
Birmingham, 321 Brown Marx Bldg.

# NEW

...from the ground up!



## .. the new Wehr A-4 Center Control Grader

Eight years of engineering development—eight years of constructive suggestions from ten thousand Wehr users all over the world—this is the structural background for the newest Wehr Grader!

Every essential demanded in a grader for modern highway work has been built into this outstanding Wehr product. Control and operation have been made as easy and effortless as possible. Scientific distribution of weight produces more power at the working points, and holds the grader to a true and steady course. Equipment is complete in every detail.

Note this partial list of specifications. A tool box, lateral adjustment of blade, control of scarifier from platform, four-speed transmission, circle and ramshorns that cannot come loose, all moving parts run in oil. Side frame 9-in. channel members, rigidly trussed with eight tubular and channel members, blade adjustment 22 degrees forward and backward, "A" frame so strong and stiff that it cannot buckle or weave, and a long list of other features.

If you want to know all the detailed advantages of the New Wehr A-4, write for complete list of specifications today.

WEHR COMPANY, Milwaukee, Wis.


(Factory at Cudahy, Wis.)





Road Building and Maintenance Equipment The new Webr A-4 Grader is powered with the McCormick-Deering tractor This job can also be supplied with Case. Fordson or United Tractor Power Plants. This model can be furnished with the new Model J-4 Webr Crawlers or Webr All-Purpose Wheels.

The steering gear on the A-4 will last the life of the grader. A child can operate the gear shift, the efficient brake stops this 10.000 limachine dead on the spot, the blade and scarifier wheels can be spun either up or down. This is a great new grader—write for gll the facts today!



## STREET HOISTS

Electric-Gasoline-Steam

Machine-cut gears—large shafts—New Center Pinion Shaft Drive with Motor Gears enclosed in oil-tight case.

Write for Bulletin 52 for full particulars on "Electrics." Send for Bulletins on other equipment in which you are interested.

Hoists—Derricks—Cableways— Slackline Excavators

STREET BROS. MACHINE WORKS Chattanooga, Tenn.











## **TEEL SHEET**



FOR FOUNDATION, COFFERDAM AND SEWER WORK

Our REPURCHASE GUARANTEE applies ON NEW AND USED SHEETING

Efficient Engineering Staff to Assist on Any Piling Problems

RENTED **BOUGHT** 

INDHEIMER

38 South Dearborn Street

CHICAGO, ILLINOIS

NC.

Phone Central 0491

#### POSITION WANTED

#### ENGINEER Can Handle Any Job!

Estimator and Construction Superintendent, grad-uate of Chicago Technical College, open for over-tures on position with live concern. Have exten-sive experience on plant construction and general installation including steam heating, ventilation, etc., for all trades. PW-96, Construction Methods Tenth Ave. at 36th St. New York City

#### LEGAL NOTICE

STATEMENT OF THE OWNERSHIP, MANAGEMENT. CIRCULATION, ETC., REQUIRED BY THE ACT OF CONGRESS OF AUGUST 24, 1912

Of Construction Methods, published monthly at New York, N. Y., April 1, 1930.

State of New York | New Y

1. That the names and addresses of the publisher.

1. That the names and addresses of the publisher.

cditor, managing editor, and business managers are:

Publisher, McGraw-Hill Publishing Company, Inc., 10th

Ave. & 36th St., N. Y. C. Editor, Robert K. Tomlin,

10th Ave. & 36th St., N. Y. C. Managing Editor.

None. Business Manager, Willard T. Chevalier, 10th

Ave. & 36th St., N. Y. C.

2. That the owner is: (If owned by a corporation, its

mane and address must be stated and sine inventisately

None. Business Manager, Willard T. Chevalier, 10th Ave. & 36th St., N. Y. C.

2. That the owner is: (If owned by a corporation, its name and address must be stated and also immediately thereunder the names and addresses of stockholders owning or holding one per cent or more of total amount of stock. If not owned by a corporation, the names and addresses of the individual owners gust be given. If owned by a firm, company, or other unincorporated concern, its name and address, as well as those of each individual member, must be given.) McGraw-Hill Publishing Company, Inc., 10th Ave. & 36th St., N. Y. C. James H. McGraw, Jr., 10th Ave. & 36th St., N. Y. C. James H. McGraw, Jr., 10th Ave. & 36th St., N. Y. C. James H. McGraw, Jr., 10th Ave. & 36th St., N. Y. C. James H. McGraw, Jr., 20th Ave. & 36th St., N. Y. C. James H. McGraw, Jr., 20th Ave. & 36th St., N. Y. C. James H. McGraw, Jr., 20th M. C. C., Trustees for: Harold W. McGraw, 37th St., N. Y. C., Trustees for: Harold W. McGraw, J., 20th St., N. Y. C. Trustees for: Harold W. McGraw, J., 20th St., N. Y. C. Trustees for: Harold W. McGraw, 20th St., N. Y. C. Harold W. McGraw, 20th St., N. Y. C. Harold W. McGraw, 285 Madison Avenue, N. Y. C. Joseph H. McGraw, 285 Madison Avenue, N. Y. C. Joseph H.



#### LEGAL NOTICE

Bragdon, 10th Ave. & 36th St., N. Y. C. Anne Hugus Britton, 10th Ave. & 36th St., N. Y. C. Mason Britton, 10th Ave. & 36th St., N. Y. C. Mason Britton, 10th Ave. & 36th St., N. Y. C. Edgar Kohak, 10th Ave. & 36th St. N. Y. C. Edgar Kohak, 10th Ave. & 36th St. N. Y. C. Edgar Kohak, 10th Ave. & 36th St. N. Y. C. J. Malcolm Muir & Guaranty Trust Co., 6 New York, Trustees for Lida Kelly Muir, 140 Broadway, N. Y. C. F. S. Weatherby, 271 Clinton Road, Brookline, Mass. Edwin S. Wilsey, 10th Ave. & 36th St. N. Y. C. Goldman, Sachs & Co., 30 Pine Street, N. Y. C.

3. That the known bondholders, mortagees, and other security holders owning or holding 1 per cent or more of total amount of bonds, mortages, or other securities are: (If there are none, so state. None.

4. That the two paragraphs next above, giving the names of the owners, stockholders, and security holders at they appear upon the books of the company, but also, in cases where the stockholder or security holder appears upon the books of the company as trustee or in any other fiduciary relation, the name of the person or corporation for whom such trustee is acting, is given; also

#### LEGAL NOTICE

that the said two paragraphs contain statements embracing affant's full knowledge and belief as to the circumstances and conditions under which stockholders and security holders who do not appear upon the books of the company as trustees, hold stock and securities in a capacity other than that of a bona fide owner; and this affiant has no reason to believe that any other person, association, or reopporation has any interest direct or indirect in the said stock, bonds, or other securities than as so stated by him. 5. That the average number of copies of each issue of this publication soid or distributed, through the mails or otherwise, to paid subscribers during the six months preceding the date shown above is (This information is required from daily publications only.)

McGRAW-HILL PUBLISHING COMPANY, INC.

C. H. THOMPSON, Secretary.

Sworn to and subscribed before me this 31st day of March, 1930.

[SEAL]

[SEAL]

[SEAL]

[Notary Public N. Y. Co. Cik's No. 97, Reg. No. 1884. Kings Co. Cik's No. 646, Reg. No. 1089.

(My Commission expires March 30, 1931.)

#### ALPHABETICAL INDEX TO ADVERTISEMENTS

This index is published as a convenience to the reader. Every care is taken to make it accurate, but Construction Methods assumes no responsibility for errors or omissions.

	TE .	
American Fork & Hoe Co	Galion Iron Works	Owen Bucket Co
American Institute of Steel Constr., Inc	Gohi Culvert Mfrs. Assn	
American Steel & Wire Co	Greene-Tweed & Company 84	Perfection Steel Body Co
Insert 73-74	H-i- W-i C C 2	
Autocar Company 4	Haiss Mfg. Company, Geo	Ransome Concrete Mchry. Co 101 Reed-Prentice Corp
Baker Míg. Co	Hercules Motor Corp	Republic Rubber Co
Barber-Greene Co		Roebling's Sons Co., John A 6
Bay City Shovels, Inc	1	Rogers Brothers Corp 91
Bethlehem Steel Co	Ingersoll-Rand Co	Sabin Company
Blaw-Knox Co		Schramm, Inc
Broderick & Bascom Rope Co120	Jaeger Machine Co118	Searchlight Section
Brown Clutch Co115		Sterling Wheelbarrow Co 29
Browning Crane Co	Knickerbocker Co	Street Bros. Machines Works128
Bucyrus-Erie Co 9	Kohler Company	Sullivan Machinery Co
Buffalo Springfield Roller Co110	Kolesch & Co	
Buhl Company		Texas Company4th Cover
Dutier Din Company		Thew Shovel Co 67
Carey Company, Philip107	LaFrance-Republic Corp	Thomas Elevator Co118
Concrete Steel Co	Lean Company, Roderick	Toledo Pressed Steel Co96-122
Carter Co., Ralph B108	Leschen & Sons Co., A	Toledo Wheelbarrow Co114
Caterpillar Tractor Co94	Lincoln Electric Co	Truscon Steel Company104
Chain Belt Company112	Link-Belt Co	
Cleveland Rock Drill Co102	Linn Mfg. Corp	Universal Atlas Cement Co 30
Cleveland Tractor Co	Lowell Wrench Co 88	Universal Crane Co 7
Concrete Steel Co	McGraw-Hill Book Co110-116	Vulcan Iron Works—Chicago 10
Connery & Co., Inc	Mahon Company, R. C 82	
Continental Rubber Works125		Wappat Gear Works, Inc
	Metalweld, Inc	Watson-Stillman Co
Dake Engine Co	Metropolitan Paving Brick Co50-51  Mohawk Asphalt Heater Co124	Western Wheeled Scraper Co123
Dayton-Whirley Co	Moore Trench Machine Co	Williams Company, G. H90
Dixon Crucible Co., Joseph112	Morris Machine Works124	
Dobbie Fdry. & Mach. Co108	Mundy Hoisting Engine Co 116	
Dodge Bros. Corp113		
Domestic Eng. & Pump Co106	National Equipment Corp 18-19	SEARCHLIGHT SECTION
Edelblute Co., T. H	National Steel Fabric Co 75	Classified Advertising
Eisemann Magneto Corp120	Northern Conveyor Co	Classifications Page EMPLOYMENT Positions Vacant
Flintkote Roads, Inc	Novo Engine Company14-15	Positions Wanted
Foote Company		USED AND SURPLUS
Fulton Bag & Cotton Mills	Orton Crane & Shovel Co 93	EQUIPMENT
Fuller & Johnson Mfg. Co	Osgood Co	Lindheimer, S. W
P 100		Man 1989 CONSTRUCTION ASSESSED

# HOISTS DERRICKS

#### Perfect Performance:-

Designed for performance—built for endurance—Clyde hoists and derricks are an ideal combination for the contractor who wants

dependable equipment.

The illustration shows the construction of the Jefferson County Court House at Birmingham, Alabama. Southern Ferro Concrete Co., general contractors, using a Clyde 35 horsepower double drum gas hoist to handle concrete and all materials. Steel erection is by Ingalls Iron Works—using a Clyde steel erectors derrick.



# CLYDE IRON WORKS SALES CO.

DISTRIBUTORS FOR CLYDE IRON WORKS DULUTH, MINNESOTA

-BRANCHES-

New Orleans: 309 Magazine St.
PORTLAND, OREGON: 555 THURMAN ST.
SEATTLE: 3410 First Avenue South
Chicago: 11 So. LaSalle Street

MEMPHIS: 69 UNION AVENUE
NEW YORK: 856 EAST 136TH STREET
VANCOUVER, - - BRITISH COLUMBIA
1325 STANDARD BANK BLDG.



Type planke of 🍇

Mason Street, Springfield, Mass., paved in 1912 with TEXACO Asphalt Penetration Macadam by the hand-poured method. There has been no maintenance to date.

# 18 years' service is one thing



Any number of pavements have seen service for as many as eighteen years. To the average man on the street, that would sound impressive. But, to the more or less "hard-boiled" engineer or contractor, this is but a part of the story.

Before the engineer or contractor is ready to express an opinion, he wants the pavement's maintenance record. Thousands of dollars can be thrown away on repairs in eighteen years and much of the old pavement replaced.

But—eighteen years' service, without need of any expenditure for maintenance, is a record even a critical engineer or contractor can appreciate. This is the record of the TEXACO Asphalt pavement on Mason Street, an important thoroughfare of Springfield, Mass.

18
years
without repair
is another thing

# TEXACO ASPHALT

New York Philadelphia Richmond Boston Jacksonville



The Texas Company
ASPHALT SALES DEPT.

135 E. 42nd Street, New York City



Chicago Cleveland Kansas Cit; Houston Dallas Buffalo